

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - William P. Wright, Deputy Surveyor, under Contract No. 514, dated Aug. 27, 1884 (DCSO records Vol. 6 Page(s) 2317)

-----  
Set post 4" dia., 4 ft. long, with marked stone 12" in ground for 1/4 sec. cor. mkd: 1/4 S on W face, from which  
A Pine, 30" dia., bears S.36°E., 17 lks., mkd: 1/4 S BT.  
A Fir, 36" dia., bears S.14°W., 42 lks., mkd: 1/4 S BT.

Wilford Haines - For: Yoncalla Lumber Co. - May 1960 - C.S. File 51/102-1

-----  
Found - Orig. BTs, both standing.  
30" Pine S.36°E., 17 lks.  
36" Fir, S.14°W., 42 lks.  
Set - 1" x 1" x 36" T. iron.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Stone - Jerry Layne - Oct. 1965 - C.S. File 54/16-12

-----  
Found - Haines' T- iron as rec.'d in 1960 & BTs as follows:  
Orig. 30", now 36" Pine S.36°E., 11.2 ft., bark scribed "1/4 S", alive.  
Orig. 36", now 40" S.14°W., 27.7 ft., bark scribed "1/4 S" "BT", alive.  
(Because these BTs are good saw logs, we mark)  
New BTs- 8" W.Fir, N.59°E., 16.9 ft., mkd: 1/4 S8 CS BT.  
8" D.Fir, S.26°W., 43.4 ft., mkd: 1/4 S7 CS BT.  
Note - This corner lies approx. 150.00 ft., E. of ridge top, course NW on edge of change from rolling top to steep East slope.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - Terrie Plouff - Bill Stewart - Stephen Flause - Dec. 13, 1979 - C.S. File 60/34-28

-----  
Found - Haines' "T" iron capped with bronze washer reading "Wilford N. Haines, Survey Point, 239, Drain Oregon" protruding 12" from ground & firmly set.  
Orig. 4"x36" post and marked stone searched for AND NOT FOUND.  
Orig. 30" Pine, now stump 6 ft. tall, 34" DBH with old bark scribing 4 ft. high on NW side reading "1/4 S", a Haines washer on NW side of stump bears S.36°E., 11.0 ft., from Haines T iron. 1960  
(Cont. next page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Orig. 36" fir, now stump 7 ft. tall, 38" DBH w/old bark scribing from 2 to 4 ft. high on NE side scribed "¼ S BT" a Haines washer on NE side bears S.11°W., 27.7 ft., slope dist. from Haines' T-iron (rec. bearing S.14°W., and we assume dist. 27.7 ft. should be horizontal distance.)

8" Fir now stump 4 ft. tall, 9" DBH with well healed double blaze no scribing visible, bears N.61°E., 16.5 ft. from Haines' T-iron (rec. N.59°E., 16.9 ft.)

8" Fir now stump 4 ft. long 8" dia., down & burned, evidence of burned out blaze, bears S.26°W., 43.7 ft.

Because of face measurement Orig. pine and face and slope dist. and bad bearing to orig. fir, We set new monument by measuring orig. bearings and horizontal distances from root crown center of orig. BTs.

Set - 1" x 36" I.P. with brass cap attached mkd:  
DOUGLAS COUNTY SURVEYOR T23S R4W ¼ S7 S8 1979

Orig. BTs as described above are now at record bearing and distance from brass cap.

8" NE tree is now N.57°E., 16.1 ft.  
8" SW tree is now S.28°W., 43.0 ft.  
Haines' T-iron is N.43½°W., 1.2 ft.

New B0 - A boat spike stamped B0 and driven in a 26" Fir stump bears S.83°W., 33.7 ft. from brass cap.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group No. 2172 - Surveyed July/Nov. 2007 - (DCSO records Vol. 55 Page(s) 21550-1)

-----

The ¼ sec. cor. of secs. 7 & 8, perpetuated by Monrean, in 1979,, monumented with an iron post, 1" dia., firmly set, projecting 1" above the ground, with brass cap (properly) mkd from which the remains of the original bearing trees

A sawed pine stump, 35" dia., bears S.36°E., 11.2 ft. with no marks visible.

A sawed fir stump, 40" dia., bears S.17¼°W., 27.7 ft., with fragmentary scribe marks visible on the bark. (Record, S.14°W.)

and the remains of a bearing object by Monrean

A sawed fir stump, 32" dia., bears S.86¾°W., 33.7 ft., with boat spike driven into center of the top.

and new bearing trees

A fir, 10" dia., bears S. 20¾° E., 15.1 ft., mkd. ¼ S8 BT.

A fir, 9" dia., bears S. 61¾° W., 12.6 ft., mkd. ¼ S7 BT.

continued next page

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

From this corner, a point erroneously perpetuated as the ¼ sec. cor. of secs. 7 & 8 by Haines in 1960, and perpetuated by Vernon "Ray" Tracy, Douglas County Surveyors Office, in 1965 and is not utilized during the course of this survey, bears N.38°31'22"W., 1.09 ft., monumented with a "T" shaped iron rod, 1" dia., firmly set, projecting 9" above the ground, with brass disk, 1" dia., affixed to top, mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN ORE, from which the remains of a bearing tree mkd. by Tracy

A roothole bears N.64½°E., 15.6 ft., with no remains of the fir trunk.

The geographic position (NAD 1983 (CORS 96)) of the ¼ section corner of sections 7 & 8 as determined by a tie to a GPS occupation of a temporary hub, utilizing dual frequency, carrier phase GPS receivers, as calculated by the National Geodetic Survey's Online Positioning Users Service, which held as fixed National Spatial Reference System Continuously Operating Reference Stations (CORS) "CAPE BLANCO" and "DODSON BUTTE", is as follows:

Latitude: 43°35'03.20" N.

Longitude: 123°12'25.31" W.