

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor Secs 5, 6, 7, & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records Vol. 6 Page(s) 2283-84)

Set post cor. of secs. 5, 6, 7, & 8, from which
A Fir, 30" dia. bears S.50°E., 29 lks.
A Fir, 10" dia., bears S.37°W., 32 lks.
A Fir, 10" dia., bears N.40°W., 26 lks.
A Fir, 6" dia., bears N.17°E., 28 lks.

Fd. & used in GLO survey - William P. Wright, Deputy
Surveyor, under Contract No. 514, dated Aug. 27, 1884 (DCSO
records Vol. 6 Page(s) 2317)

O.F. Thiel - Dec. 1904 - C.S. File 64/48-9

Found - Old post, old trees dead.
New BTs- A Cedar 7" S.11°E., 17 lks.
A Cedar 3" N.15°E., 17 lks.

Wilford Haines - For: Yoncalla Lumber Co. - May 1960 - C.S.
File 51/102-1

Found - Scribed stake at old fence corner.
1 chain North to 70" Fir, line tree.
N.40°W., 26 lks., to rotted Fir stump.
S.50°E., 29 lks., to rotted Fir stump.
40.8 ft. East to creek.
Set - 1" x 1" x 36" T iron by stake.
Found - Scribed R.Cedar, 18" S.11°E., 12.0 ft.

Douglas Co. Surveyors Office - A. Victor Cangie - Jim Cook -
Aug. 23, 1976 - C.S. File 59/18-19

Found - A 1"x1"x36" T iron set by Haines, 1960.
A R.Cedar, 21" with previously opened blazes but no
visible scribing. It bears S.11°E., 12.0 ft. and
is tagged with location poster.
No trace of orig. BTs.
Set - 1"x30" pipe w/brass cap mkd: "DOUGLAS CO. SURVEYOR"
T23S R4W
S6|S5
S7|S8
1976
Replaced "T" iron directly next to brass cap.
(Cont. next page)

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor Secs 5, 6, 7, & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- A 17" Cedar, bears N.40°E., 17.0 ft., mkd: "T23S R4W S5 CS BT" in a double blaze.
A 23" Cedar bears N.72°W., 11.0 ft., mkd: "T23S R4W S6 CS BT" in a double blaze.
A 6" Fir, bears S.85°W., 67.5 ft., mkd: "T23S R4W S7 CS BT" in a double blaze.
A 7" Cedar bears S.6½°E., 36.0 ft., mkd: "T23S R4W S8 CS BT" in a double blaze.

Fd. Ok 10/1979 C.S. File 62/63-24
Fd. Ok by Ness, 8/1992 C.S. File 63/144
Fd. Ok by David Edwards, 7/1996 M 125-58
Fd. Ok by David Edwards, 10/2008 - M158-21

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group No. 2172 - Surveyed July/Nov. 2007 - (DCSO records Vol. 55 Page(s) 21552)

The cor. of secs. 5, 6, 7, and 8, perpetuated by O.F. Thiel, in 1904, from original evidence no longer in existence, further perpetuated by Haines in 1960, and further perpetuated by Cangie, in 1976, monumented with an iron post, 1" dia., firmly set, projecting 10" above the ground, with brass cap (properly) mkd.
from which the remains of a bearing tree mkd. by Thiel
A cedar, 31" dia., bears S.10¾°E., 11.5 ft., with a healed double blaze.
and bearing trees mkd. by Cangie
A cedar, 29" dia., bears N.41°E., 16.3 ft., with a healed double blaze.
A cedar, 15" dia., bears S.86¾°W., 66.1 ft., with a healed double blaze.
A cedar, 30" dia., bears N.68¾°W., 10.6 ft., with a healed double blaze.