

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Gordon & Gardner, Contract #52 dated Feb. 1855  
(DCSO records Vol. 6 Page(s) 2285)

-----  
Set 1/4 Sec. post from which  
A Fir, 20" dia., bears N.4°E., 134 lks.  
A Laurel, 7" dia., bears S.75°W., 66 lks.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under  
Group #895 - Surveyed June/Sept. 1976 (DCSO records Vol. 41  
Page(s) 16157)

-----  
Point for 1/4 sec. cor. at proportionate distance; there is no  
remaining evidence of the orig. corner.  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with  
brass cap mkd:  
1/4 S 29  
S 32  
T23S R4W  
1976

from which  
A Fir, 6" dia., bears N.39 1/2°E., 43 lks., mkd: 1/4 S29 BT.  
A Fir, 5" dia., bears S.4 3/4°W., 36 lks., mkd: 1/4 S32 BT.

Dan Baker - For: Weyerhaeuser Co. - 9/1994 - M 119-40

-----  
Found - 2 1/2" U.S.B.L.M. Brass Cap dated 1976  
6" rotten fir stub, N.43°E., 22.1'. Rec. N.39 1/2°E.,  
43 lks, BLM  
8" Fir, S.6°W., 23.5', closed face. Rec. S.4 3/4°W.,  
36 lks, BLM  
Set - 15" Fir, N.42°E., 46.0' to "W" nail - scribed "1/4 S29  
BT"  
12" W.Fir, S.83°E., 19.1' to "W" nail - scribed "1/4  
S32 BT"  
9" Fir, N.4°W., 19.6' to "W" nail - scribed "1/4 S29  
BT"

Fd. OK BY R. Quimby 2/2007 M152-42