

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 240340

PRIMARY CORNER DESCRIPTION Center 1/4 Corner Sec. 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Resurvey, by Dale B. Bedell, Cadastral Surveyor, Surveyed under Group No. 1601. surveyed June. 1991 thru July 1992. (D.C.S.O. records Vol. 51 Page(s)19376-77)

The center 1/4 sec. cor. of sec. 20, established and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1956 (Map file M2-66, Douglas County Records), and is accepted as the corner; monumented with a " T " shaped iron rod, 30 ins. long, 1 in. diam., firmly set, projecting 6 ins. above the ground, with a brass disk mkd. WILFORD N HAINES SURVEY POINT LS 239.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T23S R4W
C 1/4 S 20
1992

from which

A fir, 6 ins. diam., bears S. 40° E., 39 1/2 lks. dist., mkd. C 1/4 S20 BT.

A fir, 23 ins. diam., bears N. 39° W., 10 lks. dist., mkd. C 1/4 S20 BT.

Deposit iron rod alongside and white "DEEP-1" magnetic marker at the base of the stainless steel post.

David Edwards - For: Roseburg Resources - 3/2008 - M 155-14

Found - BLM BC

23" fir stump, N.39°W., 6.6'

6" fir S.40°E., is a windfall

New BT - 7" Fir N.13°E., 13.65'

4" Fir N.75°W., 16.20'