

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - William P. Wright, Deputy Surveyor, under Contract No. 514, dated Aug. 27, 1884 (DCSO records Vol. 6 Page(s) 2312)

-----  
Set post 4" dia., 4 ft. long, with marked stone 12" in ground for 1/4 sec. cor. mkd: 1/4 S on N face, from which  
A Fir, 36" dia., bears N.75°E., 60 lks., mkd: 1/4 S BT.  
A Fir, 24" dia., bears N.64°W., 31 lks., mkd: 1/4 S BT.

Wilford Haines - For: E. G. Whipple Mill - Feb. 1956 - M 2-66

-----  
Found - Both orig. BTs down & very rotten. Found a rock at proper place for 1/4 corner.  
Set - Lot marker (angle iron with brass cap inscribed "Survey Point - Wilford N. Haines #239") by rock & scribed:  
19" Fir, N.48°30'W., 8.0 ft.  
18" Fir, S.38°15'E., 17.0 ft.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #895 - Surveyed June/Sept. 1976 (DCSO records Vol. 41 Page(s) 16167)

-----  
The 1/4 secs. cor. of secs. 17 & 20, perpetuated and recorded by Haines in 1956, monumented with a 1" "T" shaped iron rod, firmly set, projecting 4" above ground, with an alum. washer mkd: RLS #239, from which the remains of the orig. BTs:

A decayed Fir stump, 36" dia., bears N.75°E., 62 lks., no marks visible. (Rec. 60 lks.)

A root hole, bears N.64°W., 31 lks., with a down & decayed Fir alongside, size indeterminate, no marks visible.

and BTs mkd. by Haines:

A Fir, 23" dia., bears N.46 1/4°W., 12 1/2 lks., with fragmentary scribe marks visible on open blaze.

A Fir, 20" dia., bears S.35°E., 27 lks., with fragmentary scribe marks visible on open blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

1/4  $\frac{S\ 17}{S\ 20}$   
T23S R4W  
1976

Reset "T" shaped iron rod alongside iron post.

(Cont. next page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Resurvey, by Dale B. Bedell, Cadastral Surveyor, Surveyed under Group No. 1601. surveyed June. 1991 thru July 1992. (DCSO records Vol. 51 Page(s)19377-78)

-----  
The ¼ sec. cor. of secs. 17 and 20, monumented with an iron post, 2½" dia., firmly set, projecting 4" above the ground, with properly marked brass cap.

from which the remains of bearing trees mkd. by Wilford N. Haines, Registered Land Surveyor No. 239, in 1956

A fir stump, 20" dia., bears S.35°E., 27 lks., with healed blaze.

A fir, 26" dia., bears N.46½°W., 12½ lks., with healed blaze.

and a new bearing tree

A fir, 21" dia., bears S.64°W., 27 lks., mkd. ¼ S20 BT. The corner is located 40 lks. E. of ridge top, bearing N & S.

-----  
David Edwards - For: Roseburg Resources - 3/2008 - M 155-14

Found - BLM BC

26" fir bears N.46½°W., 83 ft./HB

21" fir stump bears S.64°W., 17.8'

Unrecorded BT w/BLM Tag:

A 3" fir bears S.14¼°W., 28.4'

-----  
BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group No. 2172 - Surveyed July/Nov. 2007 - (DCSO records Vol. 55 Page(s) 21544)

-----  
The ¼ sec. cor. of secs. 17 and 20, monumented with an iron post, 2½" dia., firmly set, projecting 4" above the ground, (with a "T" shaped iron rod, 1" dia., firmly set alongside, projecting 2" above the ground, with 1" dia. brass disk mkd. SURVEY POINT WILFORD N HAINES 239 DRAIN ORE affixed to top), with brass cap (properly) mkd.

from which the remains of bearing trees mkd. by Haines in 1960, reported by Bedell

A sawed fir stump, 20" dia., bears S.35°E., 17.8 ft., with a healed blaze.

A fir, 30" dia., bears N.46½°W., 8.3 ft., with a healed blaze.

and the remains of a bearing tree mkd. by Bedell

A sawed fir stump, 21" dia., bears S.64°W., 17.8 ft., with a healed blaze.

and a new bearing tree

A fir, 5" dia., bears S.14¼°E., 28.4 ft., mkd. X BT