

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #658 dated May 21, 1896 (DCSO records Vol. 7 Page(s) 3072)

At the intersection on N. bdy., I set a Fir post 3 ft. long, 4" sq., 24" in the ground for closing cor. of secs. 4 & 5 marked C C T24S R4W on S.; S4 on E.; and S5 on W. faces with 4 grooves on E. and 2 grooves on W. face, from which
A Maple 30" dia., bears S.40°E., 36 lks. dist. mkd. T24S R4W S4 BT.
A Maple 12" dia., bears S.72°W., 42 lks. dist. mkd. T24S R4W S5 BT.
All marks on the old witness trees referring to the new work were effaced or corrected.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; Mike Stone, crew - Feb/March 1963 - C.S. File 53/9-3

Found - 30" Maple S.40°E., 23.8 ft. scribing visible on old face opened several years ago, "R4W S4 BT", main trunk of tree broken off 5 ft. above ground, badly rotted.
Rotten Maple stump, S.72°W., 27.7 ft., broken trunk of tree lying alongside, axe marks visible, but no scribing found.
Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 4 W
C C S 5 | S 4
1963
New BTs- 16" W.Fir S.1°E., 55.6 ft. mkd. T24S R4W CC S4 CSBT
11" I.Cedar S.77½°W., 86.4 ft. mkd. T24S R4W CC S5 CS BT.
Corner lies on a bench just below steep North face of mountain.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #979, surveyed May/Sept. 1979 - (DCSO records Vol. 42 Page(s) 16402-03)

(39.43 chs.)
The original closing cor. of secs. 4 & 5, perpetuated and recorded by Godfrey in 1963, monumented with an iron post 1¼" dia., firmly set, projecting 8" above ground with brass cap mkd. in 1963, from which an original bearing tree:
A Maple 34" dia., bears S.40°E., 38 lks. dist., with healed blaze. (Rec. 36 lks.)
and bearing trees mkd. by Godfrey:
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION C C for Secs. 4 & 5 only, T24-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Grand Fir 22" dia., bears S.1°E., 86 lks. dist., with healed blaze.
 A Cedar 15" dia., bears S.76°W., 131 lks. dist., with healed blaze.
 (N.0°44'W., 39.50 chs.)
 True point for the closing cor. of secs. 4 and 5.
 Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap mkd. T 23 S R 4 W

S 32
S 5 S 4
C C

T 24 S R 4 W
1979

from which
 A basalt boulder 2½ x 2½ x 2 ft. above ground, bears S.56½°E., 9 lks. dist., mkd. X BO on top.
 A basalt boulder 2½ x 1 x 1 ft. above ground, bears S.19°W., 9 lks. dist., mkd. X BO on top.
 From this point, the cor. of secs. 32 and 33 only, T23S R4W bears S.89°44'E., 2.74 chs. dist.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2210, surveyed Oct./Nov. 2008 - (DCSO records Vol. 57 Page(s) 22353-4)

The closing cor. of secs. 4 & 5, monumented with an iron post, 2½" dia., firmly set, projecting 4" above the ground, with brass cap (properly) mkd.
 from which accessories mkd. by Jelley in 1979
 A basalt stone, 2½x2½x2 ft. above ground, bears S.47½°E., 6.5 ft., with chisel marks X BO visible on top. (Record, S.56½°E., 5.9 ft.)
 A basalt stone, 2½x1x1 ft. above ground, bears S.19°W., 5.9 ft., with chisel marks X BO visible on top.
 From this cor., the original closing cor. of secs. 4 & 5, bears S.0°44'27"E., 4.85 ft. monumented with an iron post, 1¼" dia., firmly set, projecting 11" above the ground, with brass cap (properly) mkd.
 from which the remaining original bearing tree
 A maple, 26" dia., bears S.40°E., 25.1 ft., with a healed blaze.
 and BTs mkd. by Godfrey, in 1963, reported by Jelley in 1979
 A fir, 33" dia., bears S.1°E., 55.2 ft., with a healed blaze. (Record, 56.8 ft.)
 A cedar, 27" dia., bears S.74¼°W., 108.0 ft., with a healed blaze. (Record, S.76°W., 86.5 ft.)