TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 32 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855 (DCSO records Vol. 6 Page(s) 2277)

Set ¼ Sec. post from which
An Oak, 8" dia., bears N.5°E., 65 lks.
A Y.Oak, 10" dia., bears S.40°W., 84 lks.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #895 - Surveyed June/Sept. 1976 (DCSO records Vol. 41 Page(s) 16151)

Point for ¼ sec. cor. at proportionate distance; there is no remaining evidence of the orig. corner.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

¼
S 32|S 33
T 23 S R 4 W
1976

from which
A Fir, 12" dia., bears N.28½°E., 16 lks.
A Fir, 6" dia., bears N.73°W., 22½ lks.

Fd. Ok by Dan Baker - 9/1994 - M 119-38

Fd. & used on BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert Browning, Surveying Technician under Group #1955, surveyed 2000/2001 (DCSO rec. Vol. 54 pg(s) 20894-5)