

PRIMARY CORNER DESCRIPTION Cor. Secs 28, 29, 32, & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855 (DCSO records Vol. 6 Page(s) 2277)

Set post for secs. 28, 29, 32, & 33, from which

- A Fir, 4" dia., bears N.10°E., 31 lks.
- A fir, 8" dia., bears N.80°W., 26 lks.
- A Fir, 20" dia., bears S.60°W., 110 lks.
- An Ash, 20" dia., bears S.38°E., 39 lks.

Douglas Co. Surveyors Office - H.L. Eppstein, County Surveyor NE Richardson, BA Lane, Witnesses - 8/4/1932 - "Old" Corners book Pg. 33

Set cor. from one old BT. Reset with iron 7/8" x 30", from which:

- 18" W.Oak, bears N.9°E., 90 ft.
- 30" Cedar, bears S.28°E., 240.7 ft.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Mike Stone - March 1963 - C.S. File 53/9-125

Found - 42" Cedar, S.28°E., 240.7 ft., scribing visible in previously opened scar "3 R4W BT" Tree alive & in good condition.

- 30" W.Oak, N.9°E., 90.0 ft., 2 good scars visible, did not open.

Did not find iron bar set by Eppstein. (1932)

Set - Brass cap at cor. mkd:

COUNTY SURVEYORS T23S R4W	<u>S29</u>	<u>S28</u>
OFFICE 1963	<u>S32</u>	<u>S33</u>

New BT - 13" Ash, S.28°W., 18.3 ft., mkd: T23S R4W S32 CS BT.
No trees available to NW

Note - Corner falls in fence corner, fenced North, South, and East from corner.

Glen McChesney - For: Weyerhauser Co. - 4/5/1976 -C.S. File 58/8-16

Found the Douglas County 1963 Brass cap at fence corner, N.28°E., from a scribed 16" Ash. Also, observed, but did not measure to a 42" I.Cedar, with visible scribing S.28°E., approx. 240 ft., and a forked W.Oak, faces completely healed over N.11°E., approx. 90'.

Made 1 corner reference, with W Nail and plate on: 14" D.Fir, S.54°E., 91.6'.

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor Secs 28, 29, 32, & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #895 - Surveyed June/Sept. 1976 (DCSO records Vol. 41 Page(s) 16152)

The sec. cor., perpetuated and recorded by Eppstein in 1932, from evidence no longer in existence, and further perpetuated by Godfrey in 1963, monumented with an iron post 1¼" dia, firmly set, projecting 10" above ground with brass cap properly mkd.

- from which bearing trees mkd. by Eppstein
 - A W.Oak, 32" dia., bears N.9°E., 136½ lks., with healed blaze.
 - A Cedar, 50" dia., bears S.28°E., 364 lks., with scribe marks T2 R4W CS BT visible.
- and a bearing tree marked by Godfrey
 - An Ash, 15" dia., bears S.28°W., 27½ lks., with scribe marks 4W S32 visible on open blaze.
- and a bearing tree of which I have no record
 - A Fir, 14" dia., bears S.54°E., 139 lks., with a nail with "W" embossed on head, at base.

Daniel Baker, for Weyerhaeuser Co. Sept. 1994 - M119-38.

-
- Found - Douglas County Brass cap dated 1963.
 - 32" W.Oak, N.9°E., 90.1 ft. - uprooted remains (rec. N.9°E., 90.0 ft.) 1932 Douglas County.
 - 56" Cedar, S.28°E., 240.2 ft. (rec. S.28°E., 240.7 ft.) 1932 Douglas County.
 - 19" Ash, S.28°W., 18.0 ft., closed face (rec. S.28°W., 18.3 ft.) 1963 Douglas County.
 - 18" Fir, S.54°E., 91.6 ft. to "W" nail.
 - Set - 8" Ash, N.6°W. 16.4 ft. to "W" nail. mkd. "T23S R4W S29 BT"

Fd. OK BY R. Quimby 2/2007 M152-42