

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - June 27, 1985 - C.S. File 62/28-11

Found - 1976 BLM brass cap on a 2" iron pipe, protrudes 2" above ground and leaning 11" West. Cap is properly marked.
No evidence of orig. BTs found. (Base of monument uncovered and plum position determined, bearing and distances checked from plumb position.
Haines' T-iron (top of pin bent 7" SW, measurements taken to plumb base) bears S.52°E., 8.6 ft.
Measuring from Haines' T-iron, 3 Haines' BTs are found:
22" Fir, now a 34" DBH D.Fir bears S.22°E., 33.4 ft. Tree has evidence of lower blaze and large chopped out upper blaze.
10" Cedar, now a 16" DBH I.Cedar with a partially healed double blaze showing fragmentary scribing and a Haines' BT washer on lower blaze, stamped Wilford Haines, 239, Survey Point., bears N.73°W., 58.5 ft.
An 8" D.Fir, now an 18" DBH D.Fir w/fully healed double blaze, bears S.54°W., 70.0 ft.
From 1976 dependent resurvey, 2 BTs as measured from brass cap monument:
8" Madrone, now a 7" DBH Madrone bark scribed T23S R4W S16 BT, bears N.76 3/4°E., 31.2 ft. (Rec. N.75°E., 55.44 ft.)
7" Fir, now a 9" DBH D.Fir w/fully healed double blaze bears S.76°E., 39.1 ft. (Rec. S.74 1/4°E., 39.9 ft) this dist. is level dist. from cap to center of tree trunk approx. 6 ft. above ground.
Set - Because of reasonable agreement with record, both monuments are restored to plumb position. BLM now firmly set and protrudes 4" from ground. Haines' T-iron accessory to above monument now firmly set and protruding 1" above ground.
New BTs- Haines' NW & SW BTs have blazes very closely facing BLM brass cap; these are now measured and recorded as new accessories to BLM brass cap:
An 18" DBH D.Fir with a fully healed double blazed bears S.47 1/4°W., 68.1 ft.
A 16" DBH I.Cedar with a partially healed double blaze showing fragmentary scribing and a Haines' BT washer on the lower blaze stamped Wilford Haines' 239 Survey Point, bears N.76°W., 50.6 ft.
Note - Corner is 50 ft. North beyond NW corner of small clearing & on a gentle East slope. A new Wire fence running East is 52 ft. South of BC.

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Found OK by C. Sweeden, May 2001 - LP 2001-0041