

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records Vol. 6 Page(s) 2278)

Set 1/4 Sec. post from which
 A Fir, 18" dia., bears N.15°E., 50 lks.
 A Fir, 3" dia., bears S.34°E., 73 lks.

O.F. Thiel - For: Ray Lambertson - Jan. 1948 - Thiel's FB 5
Page 1

Set a solid iron shaft, 1 1/4" x 22" long, from the old NE BT at
present the BT 42" in dia., and bears N.15°E., 50 lks. from
the corner and on fence line.

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Mike
Stone - March 1963 - C.S. File 53/9-127

Found - Old iron bar set by Thiel (see G. Langdon's
affidavit in C.S. 53/9) alongside Haines' T-iron.
(Haines' field book H-225 mentions being at the
1/4 corner)
 42" D.Fir, bears N.15°E., 33.0 ft. renewal scribing
 visible on badly charred face "S", also fragments
 of other scribed marks. This Orig. NE BT (see
 affidavit)
 No trace of SE BT.
Rescribe-
 42" D.Fir, N.15°E., 33.0 ft. "1/4 S28 CS BT"
 No other trees near.
Corner lies in fence corner, fences N., S., and West from
corner.

Frank O. Williams by Glen McChesney - For: Weyerhaeuser Co. -
April 5, 1976 - C.S. File 58/8-15

Found - 18" now 42" Fir, scribing visible, bears N.15°E.,
 33.0 ft. Orig. 1855 survey. Scribing in fire
 charred face.
 No trace of post or SE BT.
 Iron bar set by Thiel and Haines' T-iron alongside.
 Iron bar & NE BT is supported by G. Langdon's
 affidavit in C.S. File 53/9.
New BT - 10" Madrone bears West, 21.0 ft., with "W" nail and
 plate.
Corner point is about 1 ft. East of fence corner, fenced to
West & South.

(Cont. next page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #895 - Surveyed June/Sept. 1976 (DCSO records Vol. 41 Page(s) 16152-53)

Point for 1/4 sec. cor., perpetuated and recorded by Godfrey in 1963, monumented with a 1" "T" shaped iron rod, firmly set, projecting 4" above ground, with an aluminum washer mkd: RLS 239, from which the remains of the orig. BT:

A Fir, 44" dia., bears N.15°E., 50 lks., with fragmentary marks visible on open blaze.

and a bearing tree of which I have no record

A Madrone, 6" dia., bears S.88°W., 32 lks., with a nail with "W" embossed on head, at base.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

$\frac{1}{4} \begin{array}{l} S \ 28 \\ S \ 33 \end{array}$
T 23 S R 4 W
1976

Reset "T" shaped iron rod alongside iron post.

Fd. 9/1990 - M 110-58

Daniel Baker - For Weyerhaeuser Co. - Sept. 1994 - M119-38

Found - 2 1/2" BLM brass cap dated 1976.
52" Fir snag, N.21°E., 34.1 ft., closed face(rec. N.15°E., 50 lks. - 1855 GLO

Set - 10" Madrone, WEST 21.0 ft. to "W" nail, 1976 Weyco.
9" Fir, N.6°W., 39.8 ft. to "W" nail, scribed "1/4 S28 BT"

6" Fir, N.77°W., 19.3 ft. to "W" nail, scribed "1/4 S28 BT"

6" Fir, S.47°W., 9.5 ft. to "W" nail, scribed "1/4 S33 BT"

Fd. & used on BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert Browning, Surveying Technician under Group #1955, surveyed 2000/2001 (DCSO rec. Vol. 54 pg(s) 20891-2)