

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 340540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Douglas Co. Surveyors Office - Arthur Boyer, County Surveyor - J.H. Wittmeyer &amp; Chas. Neal, Witnesses - Dec. 30, 1937 &amp; Jan. 1, 1938 - "Old" Cor. Vol. 1, Renewed Corners - C.S. File 30/52</p> <p>-----</p> <p>Set - 4"x4" Cedar post for cor. from which 14" Cedar, bears S.34°W., 14 ft. 6" Cedar, bears S.83½°E., 23 ft.</p>
<p>Douglas Co. Surveyors Office - R. B. Kimberling - P. L. Earle - May 24, 1978 - C.S. File 60/11-11</p> <p>-----</p> <p>Found - A 4" x 4" squared Cedar post is stapled in fence wire, with scribing "Cen Sec 9" 1938 A 14", now 16", Cedar stump has been pushed over, orig. position approx. bears S.34°W., 14 ft. A 6", now 18" Cedar bears S.83½°E., 23.0 ft., with a chopped open blaze and bark scribing "Cen".</p> <p>Set - A 1" x 36" IP with a Brass cap set 4" above ground and marked: DOUGLAS COUNTY SURVEYOR T 23 S R 4 W C ¼ S 9 1978</p> <p>New BT - A 6" D.Fir, bears N.5°E., 9.8 ft., I double blaze and mark "C ¼ S9 T23S R4W CS BT"</p> <p>Corner is on a South slope and 1.0 ft. south of a fence corner West &amp; North, SE corner of a clear cut unit.</p>
<p>Fd. Ok by Ken Hoffine, April 1998 - M 128-60</p>
<p>FD &amp; used on BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor &amp; Robert Browning, Surveying Technician under Group #1955, surveyed 2000/2001 (DCSO rec. Vol. 54 pg(s) 20874-5)</p>
<p>1</p>