

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 377100

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4 only, T24-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #658 dated May 21, 1896 (DCSO records Vol. 7 Page(s) 3071)

I set at the intersection, a Cedar post 3 ft. long, 4" sq., 24" in the ground for closing cor. of secs. 3 & 4, mkd. C C T24S R4W on S.; S3 on E. and S4 on W. faces, with 3 grooves on E. and W. faces, from which

A Fir 30" dia., bears S.1°W., 28 lks. dist. mkd. T24S R4W S4 BT.

A Fir 30" dia., bears S.56°E., 35 lks. dist. mkd. T24S R4W S3 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; C. Putnam, crew - Aug. 27, 1959 - C.S. File 49/124

Found - Orig. 30" now 38" R.Fir S.56°E., 23.1 ft., shows good scar. I do not open.

Orig. 30" now 40" R.Fir S.1°W., 18.5 ft., previously opened, shows good scribing "BT".

Set Brass cap at cor. mkd: County Surveyors Office

T 23 S
C C S 33 R4W
 S 4 | S 3
 1959

New BTs- 38" (orig.) R.Fir bears S.56°E., 24.3 ft. scribed CC S3 T24S R4W CS BT.

6" Cedar bears S.43°W., 34.5 ft. scribed CC S4 CS BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; Mike Stone, crew - March/April 1963 - C.S. File 53/9-5

Found - Brass cap set by County Surveyor, 1959.
Orig. SW. BT, 40" D.Fir S.1°W., 18.5 ft., alive and standing.

6" Cedar S.43°W., 34.5 ft. in good condition.

Orig. SE. BT, now uprooted and down.

New BT - 11" Red Cedar S.69°E., 63.8 ft. mkd. T24S R4W CC S3 CS BT.

Fd. and used in BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #895, surveyed 1976 - (DCSO records Vol. 41 Page(s) 16132)

continued next page

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4 only, T24-4

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2168, Surveyed May/Nov. 2007 - DCSO records Vol. 57 Pages 22609-10

 True point for the closing cor. of secs. 3 and 4.
 Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd.

T23S	R4W
<hr style="width: 50px; margin: 0 auto;"/>	
S 33	
S 4	S 3
C C	
T24S	R4W
2007	

from which
 A hemlock, 6" dia., bears S.53¼°E., 3.4 ft., mkd. T24S R4W S3 CC BT.
 A cedar, 21" dia., bears S.79½°W., 33.0 ft., mkd. T24S R4W S4 CC BT.
 Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor., the closing cor. of secs. 3 & 4 bears N.0°39'02"W., 2.41 ft., perpetuated by Byron, in 1959, Godfrey, in 1963, monumented with an iron post, 1¼" dia., firmly set, projecting 15" above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T23S R4W S33 CC S4 S3 T24S 1959, from which the remains of the orig. bearing trees

A fallen, sawed, decayed fir stump, size indeterminate, bears S.56¾°E., 24.9 ft., with no marks visible. (Record, S.36°E., 23.1 ft.)

A fir, 59" dia., bears S.1°W., 18.5 ft., with a healed blaze.

and remains of a BT mkd. by Byron

A fallen, sawed, decayed cedar stump, 8" dia., bears S.34½°W., 42.0 ft., with no marks visible. (Record, S.43°W., 34.6 ft.)

and bearing tree mkd. by Godfrey

A cedar, 37" dia., bears S.69°E., 62.0 ft., with a healed blaze.

Added the marks "AM" to the brass cap
 From this same cor., the cor. of secs. 33 and 34 only, T23S R4W bears S.89°59'32"E., 196.53 ft.