

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor Secs 21, 22, 27, & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855 (DCSO records Vol. 6 Page(s) 2276)

Set post cor. of secs., from which
 A Y.Oak, 1" dia., bears S.82°E., 77 lks.
 A Y.Oak, 12" dia., bears N.66°E., 76 lks.
 A Y.Oak, 10" dia., bears N.2°W., 107 lks.
 A Y.Oak, 12" dia., bears S.9°W., 440 lks.

Fd. & used in Original GLO - William P. Wright, Deputy Surveyor, under Contract No. 514, dated Aug. 27, 1884 (DCSO records Vol. 6 Page(s) 2308-09)

Bruce Shaner - For: Pacific Power & Light Co. - Feb. 13, 1974 - M 49-55

At the sec. cor. which lies at the intersection of a very old North-South fence line, and an extension of a very old fence line from the West, and an old growth timber cutting line to the East, which point of intersection, according to witness Kathryn M. Howard, is to her knowledge the location of the orig. sec. corner.
Set - Brass cap mkd: T23S R4W S21, S22, S28, S27 1974
 8" D.Fir scribed "T23S R4W S21 BT" bears N.62°W., 45.9'
 28" D.Fir scribed "T23S R4W S22 BT" bears N.88°E. 13.0'
 28" D.Fir scribed "T23S R4W S27 BT" bears S.50°E. 18.7'
 6" D.Fir scribed "T23S R4W S28 BT" bears S.66°W., 43.1'
No orig. BTs found.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #895 - Surveyed June/Sept. 1976 (DCSO records Vol. 41 Page(s) 16148-49)

The sec. cor. perpetuated and recorded by Shaner in 1974, from testimony of local land owners and at the intersection of very old fence lines extending N., S., & W. This position is accepted as the best available evidence of the orig. corner, and is monumented with an iron post, 1½" dia., firmly set, projecting 6" above ground, with properly mkd. brass cap.
from which BTs mkd. by Shaner
 A Fir, 28" dia., bears N.85¼°E., 19½ lks., with healed blaze.
 A Fir, 28" dia., bears S.53¼°E., 28 lks., with fragmentary scribe marks visible on partially open blaze.
 A Fir, 7" dia., bears S.68¼°W., 65 lks., with fragmentary scribe marks visible on partially open blaze.
(Cont. next page)

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs 21, 22, 27, & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir, 9" dia., bears N.64 3/4°W., 69½ lks., w/fragmentary scribe marks visible on partially open blaze.
Fd. Ok 1/1990 by Hoffine C.S. File 63/104-37&38 Fd. Ok 7/1990 - M 110-41
Daniel A Renton, Minister-Glaeser Surveying - Garrett Finch & Crew - For: US Department of Interior, BLM - Great Expectation & Fast Lane -Task B -Jan 16, 2023 - M178-72 A-F ----- Found - 2½" brass cap (properly mkd) 0.5 ft above ground in good condition from which: 24" Fir bears N.61°W., 45.6 ft to side center, with scabbed blaze & BT sign (1974) 10" Fir snag bears S.66°W., 43.1 ft to side center, with scabbed blaze & BT/BLM signs (1974) 36" stump (1.5 ft high) bears S.48°E., 18.5 ft to center stump (1974) 24" stump (4 ft high) bears N.86°E., 13.1 ft to center stump removed bark with scribe marks T23S R4W S22 BT (1974) New - 21" Fir bears S.40°E., 39.6 ft mkd "T23S R4W S27 BT" 10" Fir bears N.30°E., 3.4 ft mkd "T23S R4W S22 BT" 16" Fir bears S.72°W., 44.3 ft mkd "T23S R4W S28 BT" Set chaining nail at side center, BT signs on front and rear, and painted red band for existing BTs Set chaining nail at side center, nail and washer stamped "PLS 2830" at base of blaze, BT signs on front and back and painted red band for new BT.
2