

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records Vol. 6 Page(s) 2274)

Set post for sec. cor. from which:
A Fir, 36" dia., bears N.15°E., 27 lks.
A Fir, 40" dia., bears N.45°W., 44 lks.
A Maple, 10" dia., bears S.31°W., 23 lks.
A Yew, 10" dia., bears S.35°E., 56 lks.

Wilford Haines - For: E.G. Whipple Mill - June 1961 - M22-6
(& C.S. 54/16-23Q added 3/13/2018)

Found - 40" Fir, N.45°W., 44 lks., now snag.
Set - 1"x1"x36" T-iron & scribed.
4" Fir, N.13°E., 10.5 ft.
6" Fir, S.71°W., 16.0 ft.
12" Maple S.16°W., 17.0 ft.

BLM resurvey by C. Albert White & Donald R. Beck, Cadastral
Surveyors, under Group #243 & #350 - Surveyed April/June 1963
(DCSO records Vol. 32 Page(s) 13266-67)

From the cor. of secs. 3, 4, 9, & 10, determined at record
distance from the remaining OBTs:
A Fir, 40" dia., fallen to the SE, bears N.37½°E., 27
lks., mkd. with partial scribe mks., on an opened
blaze. (Rec. bearing N.15°E.)
A Fir snag, 45" dia., bears N.39°W., 44 lks., mkd. T23S
R4W S4 BT, in the bark. (Rec. bearing, N.45°W.)
and trees mkd. by Haines in 1961:
A Fir, 6" dia., bears N.35°E., 17 lks., mkd: T23S R4W S3
BT, on a healing blaze.
A Maple, 13" dia., bears S.5°W., 25 lks., mkd: 363 T23S
R4W S9 BT, on open blaze.
A Fir, 8" dia., bears S.59°W., 20 lks., mkd. with a healed
blaze.

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with
brass cap mkd: T 23 S R 4 W
 S 4 | S 3
 S 9 | S10
 1963

from which a new BT:
A Fir, 14" dia., bears S.25°E., 153 lks., mkd: T23S R4W
S10 BT.
No suitable tree in sec. 4 within limits.

continued next page

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert Browning, Surveying Technician under Group #1955, surveyed 2000/2001 (DCSO rec. Vol. 54 pg(s) 20856-7)

The cor. of secs. 3, 4, 9, & 10, monumented with an iron post, firmly set, projecting 6" above the ground, with brass cap (properly) mkd.

from which bearing trees mkd. by Haines, in 1962,
A fir, 18" dia., bears N.35°E., 11.2 ft., with a healed blaze.

A maple, 14" dia., bears S.3¾°W., 17.5 ft., with a healed blaze. (Record, S.5°W., 16.5 ft.)

A fir, 21" dia., bears S.59°W., 13.2 ft., with a healed blaze.

and a new bearing tree

A fir, 9" dia., bears S.17°E., 16.4 ft., mkd. T23S R4W S10 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

From this point, a point established by Haines, in 1962, as the cor. of secs. 3, 4, 9, & 10, bears S.74°42'45"E., 3.86 ft., monumented with a 1x1" "T" shaped iron rod, firmly set, projecting 12" above the ground. **This point was not properly positioned and is not utilized during the course of this survey.**