TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855 (DCSO records Vol. 6 Page(s) 2274)

Set ¼ Sec. post from which
A W.Oak, 10" dia., bears N.15°W., 1560 lks.
A W.Oak, 18" dia., bears N.17°30'E., 843 lks.

BLM resurvey by C. Albert White & Donald R. Beck, Cadastral Surveyors, under Group #243 & #350 - Surveyed April/June 1963 (DCSO records Vol. 32 Page(s) 13268)

Point for the ¼ sec. corner at proportionate distance; there is no remaining evidence of the orig. corner.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

¼
S 4|S 3
T 23 S|R 4 W
1963

from which
A Cedar, 10" dia., bears N.65¼°E., 620 lks., mkd: ¼ S3 BT.
A Fir, 7" dia., bears S.27½°W., 531 lks., mkd: ¼ S4 BT.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert Browning, Surveying Technician under Group #1955, surveyed 2000/2001 (DCSO rec. Vol. 54 pg(s) 20860-1)

The ¼ sec. cor. of secs. 3 & 4, monumented with an iron post, firmly set, projecting 6" above the ground, with brass cap (properly) mkd.
from which new reference monuments
An aluminum rod, ¾" dia., 36" long, set 36" in the ground for a reference monument, bears S.27°08'07" E., 28.8 ft., with aluminum cap mkd. RM T23SR4W ¼ S3 2001 28.8 FT. TO COR and an arrow pointing to the corner.
An aluminum rod, ¾" dia., 36" long, set 36" in the ground for a reference monument, bears S.62°37'48"E., 40.8 ft., with aluminum cap mkd. RM T23SR4W ¼ S4 2001 40.8 FT. TO COR and an arrow pointing to the corner.