

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 440440

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert Browning, Surveying Technician under Group #1955, surveyed 2000/2001 (DCSO rec. Vol. 54 pg(s) 20887)

-----  
Point for the center ¼ sec. cor. of sec. 15, at intersection with the E & W centerline.  
Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, with brass cap mkd.

T23S R4W  
C ¼ S 15  
2000

from which

A fir, 9" dia., bears N.70½°E., 45.7 ft., mkd. C¼ S15 BT.  
A fir, 27" dia., bears S.18½°W., 162.7 ft., mkd. C¼ S15 BT  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

Deposit a magnet in a white plastic case at the base of the stainless steel post.  
Corner is located East, 40.0 ft., from a woven wire fence, fences extending N.35°E. and S.35°W.