

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records Vol. 6 Page(s) 2293)

Set ¼ Sec. post from which
 A Fir, 8" dia., bears S.40°E., 26 lks.
 A Cedar, 12" dia., bears N.5°W., 21 lks.

Survey by Wilford N. Haines - For: E.G. Whipple Mill - June
1961 - M 22-6

Found - 8" Fir S.40°E., 26 lks., now 42" dia.
Set - 1" x 1" x 36" T-iron and scribed:
 34" R.Cedar, S.83°E., 23.0 ft.
 11" D.Fir, N.10¼°W., 63.3 ft.

Fd. Ok by Les Roberts 6/1996 - M 125-29

BLM Dependent resurvey by Timothy J. Moore, Cadastral
Surveyor & Robert Browning, Surveying Technician under Group
#1955, surveyed 2000/2001 (DCSO rec. Vol. 54 pg(s) 20858-9)

The ¼ sec. cor. of secs. 3 & 10, perpetuated by Haines, in
1961, subsequently recovered and utilized by Roberts in 1996,
monumented with a 1x1" "T" shaped iron rod, firmly set,
projecting 6 ins. above the ground, with brass button affixed
to top, 1 in. dia., mkd., SURVEY POINT WILFORD N HAINES 239
DRAIN ORE, from which the remains of an original bearing tree
 A sawed and decayed fir stump, 50" dia., bears S.44°E.,
 18.0 ft., with a healed blaze. (Rec S.40°E., 17.2 ft.)
and the remaining bearing tree mkd. by Haines
 A fir, 23" dia., bears N.11¼°W., 63.7 ft., with a healed
 blaze.

At the corner point
Set a stainless steel post, 28" long, 2½" dia., 26" in the
ground, directly over the "T" shaped iron rod, with brass cap
mkd.
 T23S R4W
 S 3
 ¼ S 10
 2001

from which a new bearing tree
 A hemlock, 4" dia., bears S.54¾°E., 17.6 ft. mkd. ¼ S10 BT
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail)
driven at the base right side-center.
Deposit a magnet in a white plastic case at the base of the
stainless steel post.

continued next page

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Dan Saily, Lone Rock Timber Co. - Crew: Weston Addington,
Brett Ragon, Ignacio Roman & Trevor Clemo - 3/2024 - M183-50

Found - BLM brass cap and iron pipe marked T23S R4W ¼ S3 S10
2001, as per 2000-2001 BLM Dependent Resurvey
Vol. 54 Pgs 20858-59
Rotten D.Fir stump remains as per record S.44°E.,
18.0 ft.
29" D.Fir at record N.11¼°W., 63.7 ft, with a well
healed face and tag.
13" Western R.Cedar (record Hemlock) at record
S.54¼°E., 17.6 feet, with a well healed face, tag
and magnetic nail at side center.
4' tall aluminum L-Post bears West 0.4 ft the corner
monument lies on a moderately steep North slope
approximately 150 feet south of Walker Creek. Top
of corner monument is flush with ground.