

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 440640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert Browning, Surveying Technician under Group #1955, surveyed 2000/2001 (DCSO rec. Vol. 54 pg(s) 20870)

-----  
Point for the center ¼ sec. cor. of sec. 3, at intersection with the E & W centerline.  
Set a stainless steel post, 28" long, 2½" dia., 28" in the ground, with brass cap mkd.

T23S R4W  
C ¼ S 3  
2001

from which a reference monument and a bearing tree  
An aluminum rod, 1" dia., 36" long, set 36" in the ground for a reference monument, bears N.43°49'27"E., 57.4 ft., with aluminum cap mkd. RM T23SR4W C¼ S3 2001 57.4 FT. TO COR and an arrow pointing to the corner.  
A fir, 24" dia., bears S.28¼°E., 97.4 ft., mkd. C¼ S3 BT.  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

Deposit a magnet in a white plastic case at the base of the stainless steel post.  
Corner is located S.61¼°W., 47.6 ft. from the corner of woven wire fences, fences extending north, south, and east.