

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 479100

PRIMARY CORNER DESCRIPTION C C for Secs. 2 & 3 only, T24-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 6 Page(s) 2274)

Set post cor. of secs. 2, 3, 34 and 35, from which
A Laurel 10" dia., bears S.74°W., 50 lks. dist.
A Laurel 8" dia., bears S.82°E., 15 lks. dist.
A Laurel 15" dia., bears N.69°W., 36 lks. dist.
A Laurel 12" dia., bears N.5½°E., 19 lks. dist.

GL0 survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 6 Page(s) 2319-20) and Page 2323)

(Pages 2319-20)
I make diligent search for the "established" SE. cor. of sec. 34, but fail to find any trace thereof.
I again make diligent search for the cor. of secs. 34, 35, 2 and 3, but find no sign or indication of the corner or its accessories.
Set a sand stone 12x8x8 ins., 8" in the ground for cor. of secs. 34, 35, 2 and 3, marked with 4 notches on W. and 2 notches on the E. edges; from which
A Fir 40" dia., bears S.32°E., 86 lks. dist. mkd. T24S R5W S2 BT.
A Fir 24" dia., bears S.81°W., 79 lks. dist. mkd. T24S R4W S3 BT.
A Madrona 8" dia., bears N.64°W., 36 lks. dist., mkd. T23S R4W S34 BT.
No other trees within limits; raised a mound of stone 2 ft. base, 1½ ft. high W. of cor.

(Page 2323)
Intersect E and W line, 96 lks. E of cor. of secs. 2, 3, 34 and 35 which I reestablished July 16, 1897. The falling being greater than the required limit for closing. I obliterate all marks on the bearing tree in sec. 34 and remove mound of stone.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; C. Putnam, crew - July 10, 1961 - C.S. 49/124-80

Found - Rock set by Nicklin, 1896, 2 notches on E. face and 4 notches on W. face.
Burned remnant of old Fir snag S.32°E., 56.8 ft., reverse scribing plainly visible on charred face inside snag.

(Cont. Next Page)

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 479100

PRIMARY CORNER DESCRIPTION C C for Secs. 2 & 3 only, T24-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Dead Fir snag, S.81°W., 52.1 ft., very plain axe scar visible, did not open.
Madrone tree, alive, now 22", N.64°W., 23.8 ft. Center badly rotted, no scribing visible.
Set brass cap at cor. alongside rock, mkd.
County Surveyors Office
T 24 S R 4 W
S 3 | S 2
1962
New BTs- 17" D.Fir S.47°W., 43.7 ft. mkd. T24S R4W S3 CSBT.
12" D.Fir S.65°E., 38.0 ft. mkd. T24S R4W S2 CSBT.
Haines T Iron and cap bears North 5.0 ft. from corner.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; Mike Stone, crew - June/July 1963 - C.S. File 53/9-107

Found - DCS0 brass cap set in 1962 in good condition.
12" D.Fir S.65°E., 38.0 ft. alive and in good condition.
Fir S.47°W., 43.7 ft. Broken off approx. 25 ft. above ground.
New BT - 24" D.Fir S.52°W., 92.2 ft. mkd. T24S R4W S3 CS BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #895, surveyed 1976 - (DCS0 records Vol. 41 Page(s) 16132)

The cor. of secs. 2 and 3 only, perpetuated and recorded by Godfrey in 1962, and futher perpetuated by Godfrey in 1963, monumented with an iron post 1¼" dia., firmly set, monumented with an iron post, 1¼" dia., frimy set, projecting 8" above ground, with brass cap mkd. in 1962, from which the remains of bearing trees mkd. by Nicklin and Chapman:
A Fir stump 48" dia., bears S.33½°E., 83 lks. dist., no marks visible on decayed blaze. (Rec. S.32°E., 86 lks.)
A sawed Fir stump 30" dia., bears S.81°W., 79 lks. dist., with healed blaze.
A Madrone 24" dia., bears N.64°W., 36 lks. dist., with chaining notch visible on lower portion of decayed blaze.
and the remains of bearing trees mkd. by Godfrey in 1962:
A Fir 18" dia., bears S.67°E., 57 lks. dist., with scribe marks 4S R4 visible on partially healed blaze.
A Fir snag 20" dia., bears S.44¼°W., 64½ lks. dist., with scribe marks T24S R4W S3 CS BT visible on open blaze.
(Cont. Next Page)

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 479100

PRIMARY CORNER DESCRIPTION C C for Secs. 2 and 3 only, T24-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and a bearing tree mkd. by Godfrey in 1963:
A Fir 24" dia., bears S.49 3/4°W., 133 lks. dist., with
healed blaze.
From this point, a 1" T shaped iron rod, firmly set,
projecting 8" above ground, bears N.2½°W., 0.070 chs. dist.

Fd. and used in BLM resurvey by Boyd W. Peterson, under Group
#1448, Surveyed July/Aug. 1988 - (DCSO records Vol. 49
Page(s) 18667)

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor
and Robert H Browning, Survey Tech, Under Group No. 2168,
Surveyed May/Nov. 2007 - DCSO records Vol. 57 Page(s) 22583-4

The cor. of secs. 2 & 3 only, T24S R4W on the S. bdy. of the
Tp., monumented with an iron post, 1¼" dia., firmly set,
projecting 8" above ground, with brass cap (properly) mkd.
from which the remains of the orig. bearing trees
A decayed fir stump, size indeterminate, bears S.33½°E.,
54.8 ft., with no marks visible.
A sawed fir stump, 38" dia., bears S.81°W., 52.1 ft., with
no marks visible.
A madrone, 22" dia., bears N.64°W., 23.8 ft., with no
marks visible.
and bearing tree mkd. by Godfrey, in 1962
A fir stump, 11" dia., bears S.44¼°W., 42.6 ft., with no
marks visible.
and bearing tree mkd. Godfrey, in 1962
A fir, 15" dia., bears S.67°E., 37.6 ft., with a healed
double blaze.
and bearing tree mkd. by Godfrey, in 1963
A fir, 34" dia., bears S.49½°W., 92.4 ft., with a healed
blaze. (Record, 87.8 ft.)
and new bearing tree
A fir, 16" dia., bears S.36¼°E., 27.9 ft., mkd. T24S R4W
S2 BT.
From this cor., a point established by Haines, bears
N.3°11'35"W., 4.80 ft. (Record; N.2°30'00"W., 4.62 ft.),
monumented with a "T" shaped iron rod, 1" dia., firmly set,
projecting 10" above ground, with 1" dia. brass disk mkd.
WILFORD N HAINES 239 SURVEY POINT DRAIN ORE affixed to top.