

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only, South

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 6 Page(s) 2323)

-----  
Intersect E and W line, 96 lks. E. of cor. of secs. 2, 3, 34 and 35 which I reestablished July 1897. The falling being greater than the required limit for closing. I obliterate all marks on the bearing tree in sec. 34 and remove mound of stone; and, at point of intersection, 96 lks. E. of this cor., I set a basalt stone 16x12x8 ins., 10" in the ground for closing cor. of secs. 34 and 35, marked C C on N. with 2 grooves on E. and 4 grooves on W. faces; from which


A Madrone 12" dia., bears N.78°E., 63 lks. dist. mkd. T23S R4W S35 BT.

A Madrona 8" dia., bears N.65°W., 147 lks. dist. mkd. T23S R4W S34 BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #895, surveyed 1976 - (DCSO records Vol. 41 Page(s) 16131-32)

-----  
Point for the closing cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 28" long, 2½" dia., 24" in the ground with brass cap mkd.



from which

A Fir 8" dia., bears N.10°E., 35½ lks. dist. mkd. T23S R4W S35 CC BT.

A Fir 6" dia., bears N.58¼°W., 40 lks. dist. mkd. T23S R4W S34 CC BT.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2168, Surveyed May/Nov. 2007 - DCSO records Vol. 57 Page(s) 22582-3

-----  
The closing cor. of secs 34 & 35, on the S. bdy. of the Tp., monumented with an iron post, 2½ dia., firmly set, projecting 3" above ground, with brass cap (properly) mkd.

from which bearing trees mkd. by Jelley in 1976

A fir, 21" dia., bears N.10°E., 23.4 ft., with a healed blaze.

continued next page

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only, South

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 16" dia., bears N.58¼°W., 26.4 ft., with a healed blaze.

From this cor., an unrecorded point established by Haines, bears N.10°19'55"W., 7.86 ft., monumented with a "T" shaped iron rod, 1" dia., firmly set, projecting 5" above ground, with 1" dia. brass disk mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE affixed to top.

Corner is located approximately 15 ft. southerly of the cor. of old 4-strand barbed wire fences extending N. and W.