

PRIMARY CORNER DESCRIPTION Angle Point between Secs. 34 & 35

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - William P. Wright, Deputy Surveyor, under Contract No. 514, dated Aug. 27, 1884 (DCSO records Vol. 6 Page 2301)

-----  
Set post 4" dia., 4 ft. long with marked stone 12" in ground for witness cor. to secs. 34 & 35, mkd: T23 S S35 on E, R4W S34 on W, and WC on S, face, from which:

A W.Fir, 14" dia., bears S.70°E., 18 lks., mkd: T23S R4W S35 WC BT.

A Cedar, 12" dia., bears N.87°W., 18(?) lks., mkd: T23S R4W S34 WC BT.

-----  
Fd & used in Original GLO - Carl S. Nicklin, Deputy Surveyor, under Contract No. 664, dated May 23, 1896 (DCSO records Vol. 6 Page(s) 2327)

-----  
BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #895 - Surveyed June/Sept. 1976 (DCSO records Vol. 41 Page(s) 16136-37)

-----  
The witness cor. of secs. 34 & 35, determined from the remains of the orig. BTs:

A root hole, bears S.70°E., 18 lks.

A sawed Cedar stump, 25" dia., bears S.87°W., 40½ lks, with scribe marks BT visible on open blaze. (No dist. indicated in the record of the Wright survey)

This corner became an angle point on line at the time of the completion survey by Nicklin & Chapman in 1897.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

AP  
T23S R4W  
S 34 \ S 35  
1976

from which new BTs:

A Fir, 10" dia., bears N.43¼°E., 53½ lks, mkd: AP S35 BT.

A Fir, 6" dia., bears N.32¼°W., 15 lks., mkd: AP S34 BT.

-----  
BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2168, Surveyed May/Nov. 2007 - DCSO records Vol. 57 Page(s) 22596-7

-----  
The angle point of secs. 34 & 35, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.

from which the remains of the orig. bearing trees

A roothole bears S.70°E., 11.9 ft., with no remaining evidence of the trunk.

continued next page

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 500119

PRIMARY CORNER DESCRIPTION Angle Point between Secs. 34 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A decayed cedar stump, 20" dia., bears N.87°W., 26.7 ft., with axe marks visible.  
and bearing trees mkd. by Jelley in 1976  
A fir, 24" dia., bears N.43¼°E., 35.3 ft., with a healed blaze.  
A fir, 15" dia., bears N.32¼°W., 9.9 ft., with a healed blaze.  
Corner is located 6 ft. W. of a 4 strand barbed-wire fence, extends N. and S.