TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - William P. Wright, Deputy Surveyor, under Contract No. 514, dated Aug. 27, 1884 (DCSO records Vol. 6 Page(s) 2300)

Set post 4" dia., 4 ft. long, with marked stone 12" in ground for ¼ sec. cor. mkd: ¼ S on W face, from which

A Fir, 50" dia., bears N.24°W., 10 lks., mkd: ¼ S BT.
A Fir, 24" dia., bears S.47°W., 43 lks., mkd: ¼ S BT.

Fd. & used in GLO retracement - Carl S. Nicklin, Deputy Surveyor, under Contract No. 664, dated May 23, 1896 (DCSO records Vol. 6 Page(s) 2327)

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #895 - Surveyed June/Sept. 1976 (DCSO records Vol. 41 Page(s) 16135-36)

The ¼ sec. cor. determined at rec. bearing and distance from remains of orig. BTs:

A root hole, bears S.47°W., 43 lks., with a down Fir alongside, 18" dia., no marks visible.
A sawed Fir stump, 60" dia., bears N.24°W., 10 lks., with axe marks visible on decayed blaze.

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

¼
S 34|S 35
T 23 S R 4 W
1976

from which new BTs:

A Fir, 6" dia., bears S.73½°E., 13 lks., mkd: ¼ S35 BT.
A Fir, 8" dia., bears S.36½°W., 9½ lks., mkd: ¼ S34 BT.

Fd. 1/1995 M 121-69

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2168, Surveyed May/Nov. 2007 - DCSO records Vol. 57 Page(s) 22595-6

The ¼ sec. cor. of secs. 34 and 35, monumented with an iron post, 2½" dia., firmly set, projecting 2" above ground, with brass cap (properly) mkd.
from which the remains of an orig. bearing tree

A decayed, sawed fir stump, 37" dia., bears N.24°E., 6.6 ft., with no marks visible.

and bearing trees mkd. by Jelley in 1976

A fir, 13" dia., bears S.73½°E., 8.6 ft., with a healed blaze.

continued next page

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A fir, 13" dia., bears S.36½°W., 6.3 ft., with a healed blaze.
Corner is located in a wire fence, extends N. and S.