

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs 26, 27, 34, & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - William P. Wright, Deputy Surveyor, under Contract No. 514, dated Aug. 27, 1884 (DCSO records Vol. 6 Page(s) 2299-2300)

Set post 6" dia., 4 ft. long, with marked stone 12" in ground for sec. cor. mkd: T23S S26 on NE, R4W S35 on SE, S34 on SW, S27 on NW face, with 2 notches on E and 1 on S face, from which:

- A Fir, 14" dia., bears N.47°W., 35 lks., mkd: T23S R4W S27 BT.
- A Fir, 12" dia., bears N.28°E., 41 lks., mkd: T23S R4W S26 BT.
- A Maple, 9" dia., bears S.44°E., 38 lks., mkd: T23S R4W S35 BT.
- A Maple, 8" dia., bears S.82°W., 75 lks., mkd: T23S R4W S34 BT.

Fd. & used in GLO retracement - Carl S. Nicklin, Deputy Surveyor, under Contract No. 664, dated May 23, 1896 (DCSO records Vol. 6 Page(s) 2327)

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #895 - Surveyed June/Sept. 1976 (DCSO records Vol. 41 Page(s) 16135)

From the sec. cor. determined at rec. bearing and distance from the remains of the OBTs:

- A root hole, bears N.28°E., 41 lks., with a down Fir alongside, 14" dia., with scribe marks T23S R4W S visible on bark blaze.
- A root hole, bears N.47°W., 35 lks.

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 23 S	R 4 W
S 27 S 26	
S 34 S 35	
1976	

from which new bearing trees

- A Fir, 8" dia., bears N.57 3/4°E., 13½ lks., mkd: T23S R4W S26 BT.
- A Fir, 8" dia., bears S.77¼°E., 60 lks., mkd: T23S R4W S35 BT.
- A Fir, 6" dia., bears S.34¼°W., 28½ lks., mkd: T23S R4W S34 BT.
- A Fir, 5" dia., bears N.71°W., 7½ lks., mkd: T23S R4W S27 BT.

continued next page

1

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor Secs 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2168, Surveyed May/Nov. 2007 - DCSO records Vol. 57 Page(s) 22595

The cor. of secs. 26, 27, 34, & 35, monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground, with brass cap (properly) mkd.

from which the remains of the BTs mkd. by Jelley in 1976

A roothole bears N.57¼°E., 8.9 ft., with fallen fir snag, 12" dia., lying alongside, with a healed blaze.

A fir, 13" dia., bears S.76½°E., 39.6 ft., with a healed blaze. (Record, S.77¼°E.)

A fir snag, 7" dia., bears S.34¼°W., 18.8 ft., with a healed blaze.

A fir snag, 7" dia., bears N.71°W., 5.0 ft., with a healed blaze.

and new bearing trees

A fir, 16" dia., bears N.49¼°E., 19.8 ft., mkd. T23S R4W S26 BT.

A fir, 13" dia., bears N.30°W., 34.2 ft., mkd. T23S R4W S27 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

(NAD 1983 (CORS 96))

Latitude: 43°32'00.93"N Longitude: 123°08'49.89"W

Daniel A Renton, Minister-Glaeser Surveying - Garrett Finch & Crew - For: US Department of Interior, BLM - Great Expectation & Fast Lane -Task B -Jan 2023 - M178-72 A-F

Found - 17" Fir bears S.78°E., 39.6 ft to side center, scabbed blaze with BT sign (1976)

14" Fir snag (12 ft high) bears N.22°W., 34.2 ft to side center, with partial visible scribe T23S R4W S" (2007)

20" Fir bears N.49°E., 20.3 ft to side center with scabbed blaze and BT sign (2007)

Set chaining nail at side center, BT signs on front and rear, and painted red band for existing BTs