

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor Secs 22, 23, 26, & 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - William P. Wright, Deputy Surveyor, under Contract No. 514, dated Aug. 27, 1884 (DCSO records Vol. 6 Page 2307)  
-----  
Set post 6" dia., 4 ft. long, with marked stone 12" in ground for sec. cor. mkd: T23 S23 on NE, R4W S26 on SE, S27 on SW, S22 on NW face with 2 notches on E & S edges from which:  
A Fir, 60" dia. bears S.25°E., 92 lks mkd: T23S R4W S26 BT  
A Fir, 6" dia., bears S.17°W., 25 lks., mkd: T23S R4W S27 BT.  
A Fir, 5" dia., bears N.45°W., 40 lks., mkd: T23S R4W S22 BT.  
A Cedar, 4" dia., bears N.79°E., 11 lks., mkd: T23S R4W S23 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy & crew - Nov. 1965 - C.S. File 54/16-18 (See Haines' report below)  
-----  
Found - Haines' "T" iron & 3/4" I.Pipe & following BTs:  
64" D.Fir snag, S.25°E., 60.8 ft (face) bark scribed "T23S R4W S26 BT 363" This possible Orig. BT.  
21" D.Fir, N.59°W., 49.6 ft (face) bark scribed "363 T23S R4W S22 BT"& cruisers mkd" ↙ "on face  
This corner fits calls south & west. We find no orig scribe

Wilford N. Haines - Approx. 1960 filed 12/1965 - C.S. File 54/16-23I  
-----  
Found - 60" Fir, S.25°E., 92 lks.  
6" Fir stub S.17°W., 25 lks., scribing visible on stub.  
Scribed- 14" Fir, N.60°W., 50.0 ft.  
36" Fir, S.89°W., 44.5 ft.  
60" Fir, S.25°E., 60.72 ft., bark scribed.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - Sept. 1966 - C.S. File 54/16-45  
-----  
Found - Haines' "T" iron & 3/4" IP at corner.  
Orig. 60" now 64" fir, S.25°E., 60.7 ft., re-bark scribed, now snag.  
14", now 20" D.Fir, N.60°W., 50.0 ft., bark scribed, button on face.  
36" now stump, S.89°W., 44.5 ft., bark scribed.  
New BTs- 8" Hemlock N.35°W., 22.8 ft, mkd: T23S R4W S22 CS BT  
(Cont. next page)

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs 22, 23, 26, & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

14" Hemlock N.14°E., 44.1 ft., mkd: T23S R4W S23 CS BT.  
 9" Hemlock S.62°E., 63.7 ft., mkd: T23S R4W S26 CS BT.  
 DID NOT SET BRASS CAP - Corner lies in corner of cut off unit in sec. 27.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #895 - Surveyed June/Sept. 1976 (DCSO records Vol. 41 Page(s) 16138-39)

-----

From the sec. cor. perpetuated and recorded by Haines in 1960 and further perpetuated by Tracy in 1966, monumented with a 1" "T" shaped iron rod, firmly set, projecting 10" above ground, from which the remains of the OBTs:

- A Fir snag, 65" dia., bears S.25°E., 96 lks., re-scribe T23S R4W S2 BT 363 on bark blaze by Haines, in 1960. (Rec. 92 lks., to face.)
- and the remains of bearing trees mkd. by Haines
  - A sawed Fir stump, 36" dia., bears S.89°W., 67 lks., with scribe marks 63 BT visible on bark blaze.
  - A Fir, 24" dia., bears N.60°W., 77 lks., with scribe marks T23S R4W S22 BT visible on bark blaze.
- and BTs mkd. by Tracy
  - A Hemlock, 20" dia., bears N.12 3/4°E., 67 lks., with healed blaze.
  - A Hemlock, 10" dia., bears S.63½°E., 96 lks., with fragmentary scribe marks visible on open blaze.
  - A Hemlock, 12" dia., bears N.36½°W., 34½ lks., with scribe marks T23S R S CS BT visible on open blaze.

At the corner point  
 Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 23 S	R 4 W
S 22   S 23	
S 27   S 26	
1976	

from which a new BT  
 A Fir, 8" dia., bears S.59°W., 122½ lks., mkd: T23S R4W S27 BT.  
 Reset "T" shaped iron rod alongside iron post.

Fd. & used on BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #1083 - Surveyed Nov. 1981/April 1982 (DCSO records Vol. 46 Page(s) 17542-43)

continued next page

2

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Daniel A Renton, Minister-Glaeser Surveying - Garrett Finch & Crew - For: US Department of Interior, BLM - Great Expectation and Fast Lane -Task B -Jan. 17, 2023 - M178-73A-F

-----  
Found - 3¼" BLM brass cap (properly mkd), 0.4 ft. above ground in good condition with 3/4" iron pipe & Haines 1" brass cap South of & along side.  
29" Fir snag (30 ft high) bears N.61°W., 50.0 ft., illegible bark scribe with BT sign (1960)  
28" Fir bears S.60°W., 82.4 ft to side center, with scabbed blaze (1976)  
23" Hemlock bears N.36°W., 22.8 ft to side center, scabbed blaze with BT sign (1966)  
26" Hemlock bears N.14°E., 44.0 ft to side center, scabbed blaze with BT sign (1966)  
24" Hemlock bears S.64°E., 62.8 ft to side center, scabbed blaze with BT sign (1966)  
36" stump (3 ft high) bears S.88°W., 44.5 ft to center of stump (1960)  
65" stump (3 ft high) bears S.22°E., 60.7 ft to center of stump, with illegible scribe and cruiser marks (1960)  
Set chaining nail at side center, BT signs on front and rear, and painted red band for existing BTs