

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - William P. Wright, Deputy Surveyor, under Contract No. 514, dated Aug. 27, 1884 (DCSO records Vol. 6 Page(s) 2310)

Set post 4" dia., 4 ft. long, with marked stone 12" in ground for 1/4 sec. cor. mkd: 1/4 S on W face, from which
 A Fir, 10" dia., bears S.14°W., 7 lks., mkd: 1/4 S BT.
 A Fir, 10" dia., bears N.20°E., 45 lks., mkd: 1/4 S BT.

Wilford Haines - Survey date unknown, Rec'd 1990 - H-223

Set - iron rod.
 12" Fir _____ 43.12 ft.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Stone - Jerry Layne - Nov. 1965 - C.S. File 54/16-33

Found - Haines' "T" iron, not recorded.
 Orig. 10", now 24", Fir N.20°E., 29.7 ft., shows "1/4" scribe on previously opened face.
 SW BT now only remains.
 New BTs- 9" W.Fir, S.64°W., 20.2 ft., mkd: 1/4 S22 CS BT.
 16" D.Fir, N.40°E., 52.6 ft., mkd: 1/4 S 23 CS BT.
 This corner lies on top, small spur, course SW.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #895 - Surveyed June/Sept. 1976 (DCSO records Vol. 41 Page(s) 16139-40)

The 1/4 sec. cor. perpetuated and recorded by Tracy in 1965, monumented with a 1" "T" shaped iron rod, firmly set, projecting 10" above ground, from which the remains of the orig. bearing trees:
 A Fir snag, 21" dia., bears N.20°E., 45 lks., with scribe marks 1/4 S visible on open blaze.
 and the remains of bearing trees mkd. by Tracy
 A Fir snag, 15" dia., bears N.38 1/4°E., 79 lks., with scribe marks 1/4 S23 CS BT visible on open blaze.
 A Grand Fir, 14" dia., bears S.63°W., 30 1/2 lks., with healed blaze.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

$\frac{1}{4}$
 S 22 | S 23
 T 23 S R 4 W
 1976

(Cont. next page)

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>from which a new BT A Fir, 5" dia., bears S.85 3/4°E., 70½ lks., mkd: ¼ S23 BT Reset "T" shaped iron rod alongside iron post.</p>
<p>Fd. Ok by K. Hoffine - 7/1990 - M 110-41, C.S. Files 63/104-41 & 63/106.</p>
<p>Ken Hoffine - For: Juniper Properties Limited Partnership - 2/2009 - M159-8</p> <p>-----</p> <p>Found - 1976 BLM brass cap with Haines T-Iron alongside 27" G.Fir bears S.63¼°W., 19.7 ft. (rec. S.63°W., 20.1 ft.) healed face & tag. 20" D.Fir bears S.85½°E., 46.0 ft. (rec. S.85¼°E., 46.5 ft.) healed face & tag. Corner lies on flat spur ridge approx. 120 ft. South of reprod & in BLM timber.</p>
<p style="text-align: right;">2</p>