

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 500460

PRIMARY CORNER DESCRIPTION North 1/16 Cor. Secs. 14 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

M. B. Germond (?) - 1909 or 1911 (?) - (Old) Vol. 2 Pg. 161

Set a stone, 6"x9"x18" granite, at 20.09 S from the sec. cor. (Secs. 10, 11, 14, & 15) and marked:

R.Fir 25" dia., which bears N.72°00'E., (no dist. given)
R.Fir 24" dia., which bears N.68°30'W., 53 lks. ?

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 2/4/2009 - C.S. File 67/28-14

Found - set stone plumb in old East-West fence line bottom
meas. 6"x9" 17" long top meas. 4"x6" marked "CS"
(Rec. 6"x9"x18" stone) circa 1909

No BT's found.

New - Reset stone in exact position as found. Set 5/8"x30"
long iron rod with DCSO alum. cap stamped "2009"
along North edge of stone. Center of stone bears
South 0.3 ft. I.R. protrudes 5" out of ground,
stone protrudes 3" out of ground.

Bearing & dist. taken from corner stone.

9" dia., D.Fir double blazed & scribed "N1/16 S14 CS
BT" bears N.23½°E., 15.6 ft.

14" dia. D.Fir double blazed & scribed "N1/16 S15 CS
BT" bears S.44°W., 8.8 ft.

Compass decl. 16½°E.