

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35; & 2, T24-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 6 Page(s) 2322)

Set a sandstone 12x10x10, 8" in the ground for ¼ sec. cor. marked ¼ on N. face; from which

A Fir 12' dia., bears N.7°E., 28 lks. dist. mkd. S BT.

A Fir 30" dia., bears S.82°W., 28 lks. dist. mkd. ¼ S BT
This cor. is on a hillside, sloping SW. 350 ft. below top of ridge.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; Mike Stone, crew - June 1963 - C.S. File 53/9-109

Found - 48" dead Fir snag, S.82°W., 18.5 ft. Cut open and found good scribing "B" on old face.

No trace of rock set for corner nor of NE. BT.

Set Brass cap at cor. mkd: County Surveyors Office

T 24 S R 4 W

¼ $\frac{S\ 35}{S\ 2}$

T 24 S R 4 W

1963

Corner lies in bottom of small draw at foot of a very steep SE. slope. Area surrounding corner has all been badly burned. No live trees near corner.

Rescribe in wood, 48" Fir snag, S.82°W., 18.5 ft. mkd. ¼ S2 CS BT.

New BT - 18" D.Fir West, 166.5 ft. mkd. ¼ S35 S2 CS BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #895, surveyed 1976 - (DCSO records Vol. 41 Page(s) 16131)

The ¼ sec. cor., perpetuated and recorded by Godfrey in 1963, monumented with an iron post, 1¼" dia., firmly set, projecting 8" above ground with brass cap mkd. in 1963, from which the remains of the original bearing trees:

A Fir snag 48" dia., bears S.82°W., 28 lks. dist., with scribe marks ¼ S BT visible on opened blaze. Rescribed by Godfrey in 1963, with scribe marks ¼ S35 CS BT visible on open blaze, alongside original blaze.

and the remains of a bearing tree mkd. by Godfrey:

A Fir sng 18" dia., bears West, 252 lks. dist., with healed blaze.

and a bearing object of which I have no record:

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35; & 2, T24-4

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A basalt stone 3 x 3 x 3 ft. above ground, bears N.81 3/4°W., 28 1/2 lks. dist., with chisel marks X BO visible on top.
and a new bearing object:
A conglomerate boulder 8 x 6 x 4 ft. above ground, bears S.28 3/4°W., 65 lks. dist., mkd. X BO on top.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2168, Surveyed May/Nov. 2007 - DCSO records Vol. 57 Page(s) 22582

The 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., monumented with an iron post, 1 1/4" dia., firmly set, projecting 10" above ground, in a mound of stone, 2 ft. base, 18" high, with brass cap (properly) mkd.
from which the remains of an orig. bearing tree
A decayed fir stump, size indeterminate, bears S.82°W., 18.5 ft., with no marks visible.
and the remains of a bearing tree mkd. by Godfrey, in 1963
A decayed fir stump, size indeterminate, bears S.87 1/4°W., 166.3 ft., with no marks visible. (Record, West)
and an accessory mkd. by Jelley in 1976
A conglomerate boulder, 8x6x4 ft. above ground, bears S.25 1/4°W., 50.8 ft., with no marks visible. (Record; S.28 3/4°W., 42.9 ft.)
and new bearing trees
A maple, 15" dia., bears S.8°W., 9.9 ft., mkd. 1/4 S2 BT.
A chinquapin, 10" dia., bears N.70 1/2°W., 44.3 ft., mkd. 1/4 S35 BT.
Each new bearing tree has a 2 1/2"x 1/4" magnetic nail (Mag Nail) driven at the base right side-center.