

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - William P. Wright, Deputy Surveyor, under Contract No. 514, dated Aug. 27, 1884 (DCSO records Vol. 6 Page(s) 2301)

-----

Set post 4" dia., 4 ft. long, with marked stone 12" in ground for  $\frac{1}{4}$  sec. cor. mkd:  $\frac{1}{4}$  S on N face, from which  
A Fir, 36" dia., bears N.65°W., 60 lks., mkd:  $\frac{1}{4}$  S BT.  
A Laurel, 4" dia., bears S.4 $\frac{1}{2}$ °E., 9 lks., mkd:  $\frac{1}{4}$  S BT.

Fd. & used in GLO retracement - Carl S. Nicklin, Deputy Surveyor, under Contract No. 664, dated May 23, 1896 (DCSO records Vol. 6 Page(s) 2328)

Ken Hoffine, LS 2291 - For: Lone Rock Timber Co. - Jan. 1990 - M 109-56 - C.S. File 63/106

-----

Set - 5/8" x 36" iron rod with alum. cap 0.5 ft. above ground and mark the following accessories:  
Orig. 36" D.Fir is burned and decayed 16 ft. tall 36" snag with burned out face. Bears N.65°W., 39.6 ft.  
11.5 ft. D.Fir bears S.19°E., 4.57 ft. to alum. nail in mid-base. I scribe " $\frac{1}{4}$  S 35 BT", drive a 6" spike in face and tag tree.  
14" D.Fir bears N.38°E., 20.15 ft., to alum. nail in mid-base. I scribe " $\frac{1}{4}$  S 36 BT" drive a 6" spike in face and tag tree.