

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2168, Surveyed May/Nov. 2007 - DCSO records Vol. 57 Page(s) 22597-8

The ¼ sec. cor. of secs. 23 and 26, monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground (alongside of which is a "T" shaped iron rod, 1" dia.), with aluminum cap (properly) mkd.

from which the remains of BTs mkd. by Jelley in 1981-82

A fir, 18" dia., bears N.34°E., 6.6 ft., with a healed blaze.

A roothole bears S.60°W., 9.9 ft., with fallen fir snag, 15" dia., lying alongside, with a healed blaze. and new bearing tree

A fir, 6" dia., bears S.36°E., 40.5 ft., mkd. ¼ S26 BT. Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

(NAD 1983 (CORS 96))

Latitude: 43°32'52.58"N Longitude: 123°08'14.90"W