TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias Description
Alias Description
Alias Description
Alias Description

Original - Gordon & Gardner, Contract #52 dated Feb. 1855 (DCSO records Vol. 6 Page(s) 2288)

Set ¼ sec. post, from which
A Fir, 70" dia., bears S.75°W., 20 lks.
A Fir, 15" dia., bears N.30°E., 46 lks.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #895 - Surveyed June/Sept. 1976 (DCSO records Vol. 41 Page(s) 16142)

Point for the ¼ sec. cor. of secs. 14 & 23, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

¼ S 14
S 23
T23S R4W
1976

from which
A Fir, 5" dia., bears N.67½°E., 70 lks., mkd: ¼ S14 BT.
A Fir, 18" dia., bears S.53¼°E, 58 lks., mkd: ¼ S 23 BT.

Fd. & used in BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #1083 - Surveyed Nov. 1981/April 1982 (DCSO records Vol. 46 Page(s) 17544)

Fd. Ok by D. Peel - M 113-42

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2168, Surveyed May/Nov. 2007 - DCSO records Vol. 57 Page(s) 22598

The ¼ sec. cor. of secs. 14 and 23, monumented with an iron post, 2½" dia., firmly set, projecting 1" above ground, with brass cap (properly) mkd.
from which the remains of BTs mkd. by Jelley in 1981-82
A fir, 11" dia., bears N.67½°E., 46.2 ft., with a healed blaze.
A decayed fir stump, size indeterminate, bears S.53¼°E., 38.3 ft., with no marks visible.
and new bearing tree
A hemlock, 6" dia., bears S.2½°W., 16.3 ft., mkd. ¼ S23 BT