

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records Vol. 6 Page(s) 2292)

Set ¼ Sec. post from which
 A B.Oak, 5" dia., bears S.11°E., 161 lks.
 A W.Oak, 18" dia., bears N.76°E., 477 lks.

Wilford Haines - For: E.G. Whipple Mill - June 1961 - M 22-6

Set - 1" x 1" x 36" T - iron & scribed
 10" Fir S.45°W., 13.4 ft.
 14" Fir, N.81°W., 16.2 ft.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike
Stone - Jerry Layne - Nov. 1965 - C.S. File 54/16-39

Found - Haines' "T" iron & BTs as recorded in 1961
 10" D.Fir, now dead, S.45°W., 13.4 ft., scribe
 visible.
 18" D.Fir, alive, N.81°W., 16.2 ft., scribe visible.
New BT - 14" D.Fir, S.21°E., 26.2 ft., mkd; ¼ S11 CS BT.
Note - Corner lies 30 ft. south of small dry creek, course
 west.

Ken Hoffine - For: Lone Rock Timber Co. - 10/2000 - M 135-69

Found - Haines "T" iron projecting 1.0 ft. above ground.
 A rotten D.Fir stump of indeterminate size bears
 N.82 ¾°W., 15.8 ft. (rec. N.81°W., 16.2 ft.)
 A rotten D.Fir stump of indeterminate size bears
 S.44 ¾°W., 13.4 ft. (rec. S.45°W., 13.4 ft.)
New - 9" D.Fir bears S.40½°W., 27.9 ft., we tag tree &
 scribe.
 10" D.Fir bears N.86½°W., 22.3 ft., we tag tree &
 scribe.
 22" I. Cedar bears S.87¼°E., 67.3 ft. we tag tree &
 scribe.
 20" D.Fir bears N.32°E., 55.3 ft. we tag tree &
 scribe.
 Corner lies on North slope approx. 30 ft. south of
 bottom of small draw. Draw runs east-west.

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert Browning, Surveying Technician under Group #1955, surveyed 2000/2001 (DCSO rec. Vol. 54 pg(s) 20847-8)

The 1/4 sec. cor. of secs. 2 & 11, reestablished at proportionate measurement by Haines, in 1961, perpetuated by Tracy, in 1965, further perpetuated by Hoffine. There is no remaining evidence of the original corner, therefore this point is accepted as the cor., monumented with a 1x1". "T" shaped iron rod, firmly set, projecting 13" above the ground, from which remains of BTs mkd. by Haines

A sawed & decayed fir stump, 18" dia., bears S.44 1/2°W., 13.4 ft., no marks visible.

A sawed & decayed fir stump, 20" dia., bears N.82 3/4°W., 15.8 ft., with scribe marks T visible.

and the remains of a BT mkd. by Tracy

A sawed & decayed fir stump, 12" dia., bears S.22 1/4°E., 25.2 ft., with a healed blaze.

and BTs mkd. by Hoffine

A fir, 20" dia., bears N.32 1/4°E., 55.3 ft., with scribe marks S2 1/4 BT visible on partially healed blaze.

A cedar, 22" dia., bears S.87°E., 67.3 ft., with scribe marks S11 1/4 BT visible on partially healed blaze.

A fir, 9" dia., bears S.40 3/4°W., 27.9 ft., with scribe marks S11 1/4 BT visible on partially healed blaze.

A fir, 10" dia., bears N.86 1/4°W., 22.3 ft., with scribe marks S2 1/4 BT visible on partially healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2 1/2" dia., 22" in the ground, directly over the "T" shaped iron rod, with brass cap mkd.

T23S R4W

1/4 S 2 / S 11

2001

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located South, 35.0 ft., of a ravine, drains West.

Dan Saily, Lone Rock Timber Co. - Crew: Weston Addington, Brett Ragon, Ignacio Roman & Trevor Clemo - 3/2024 - M183-50

Found - BLM brass cap and iron pipe marked 1/4 S2 S11 2001, as per 2000-2001 BLM dependent resurvey Vol. 54 Pgs 20847-48. The brass cap has corroded to the extent that the Township and Range markings are no longer visible.

Continued next page

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fir stob and stump remains at record N.82 $\frac{3}{4}$ °W., 15.8 ft. No visible marks or tag.
20"x4.5' tall Fir stump at record N.32 $\frac{1}{4}$ °E., 55.3 ft. LONE ROCK tag and partially visible scribe on a rotten face.
19"x5' tall Cedar stump at record S.87°E., 67.3 ft. partially visible scribe on a rotten face. We tag with record information
19"x7' tall D.Fir stump at record N.86 $\frac{1}{4}$ °W., 22.3 ft. LONE ROCK tag and well healed face
19"x5.5' tall D.Fir stump at record S.40 $\frac{3}{4}$ °W., 27.9 ft. LONE ROCK tag and well healed face
3' tall aluminum L-post N.55°E., 0.6 ft.
The corner monument lies approximately 40 ft South of a small creek running SW, on the East edge of a recent clearcut. Top of corner monument is 0.3 ft above ground level.