

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Wilford Haines - For: E.G. Whipple Mill - June 1961 - M 22-6

Set - 1" x 1" x 36" T - iron & scribed
6" Fir S.17°E., 34.7 ft.
18" Fir, S.62°W., 57.0 ft.

Ken Hoffine - For: Lone Rock Timber Co - 10/2000 - M 135-69

Found - Haines "T" iron projecting 0.5 ft. above ground.
27" rotten D.Fir stump bears S.60¼°W., 86.9 ft. open
face, visible scribe & tag. (Rec. S.62°W., 57.0
ft. We believe distance is typo error on Haines
Map)
New - 12" D.Fir bears S.61¼°E., 35.4 ft. We tag tree &
scribe.
15" D.Fir bears S.63°W., 38.0 ft. We tag tree &
scribe.
Corner lies on flat ground on South edge of pasture.
A fence is south 17.4 ft. Fence runs East-West.

Ken Hoffine - For: Lone Rock Timber Co - 10/2007 - 2007-0150

Found - Haines T-Iron with washer
17" D.Fir bears S.61¾°W., 35.4 ft. rec. (S.61¼°W.,
35.4 ft.) healed face & BT tag.
17" D.Fir bears S.63°W., 38.0 ft* as per rec, healed
face & BT tag.
Note - Corner lies on flat ground at south edge of pasture.
A east-west fence line bears south approx 17.5 ft