



TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. OK by Donald Peel 3/1993 - M 117-5

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2168, Surveyed May/Nov. 2007 - DCSO records Vol. 57 Pages 22589-90

-----  
The ¼ sec. cor. of secs. 35 & 36, perpetuated by Tracy, in 1965 & 1968, monumented with an iron post, 1¼" dia., firmly set, projecting 9" above ground, (alongside of which is an iron pipe, ¾" dia., firmly set, projecting 6" above ground), with brass cap (properly) mkd.

from which the remains of the orig. bearing trees

A fir snag, 52" dia., bears S.34°E., 5.9 ft., with no marks visible on an opened blaze.

A fir snag, 38" dia., bears N.35°W., 5.9 ft., with fragmentary scribe marks visible on an opened blaze. and the remains of a bearing tree mkd. by Tracy

A sawed fir stump, 15" dia., bears N.89¼°W., 31.8 ft., with a healed blaze. and new bearing trees

A chinquapin, 7" dia., bears N.32½°E., 7.7 ft., mkd. ¼ S36 BT.

A hemlock, 17" dia., bears S.37°W., 12.6 ft. mkd. ¼ S35 BT  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.