

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>Original - William P. Wright, Deputy Surveyor, under Contract No. 514, dated Aug. 27, 1884 (DCSO records Vol. 6 Page 2303)</p> <p>-----</p> <p>Set post 4" dia., 4 ft. long, with marked stone 12" in ground for 1/4 sec. cor. mkd: 1/4 S on W face, from which</p> <p> A Fir, 50" dia., bears N.37°E., 12 lks., mkd: 1/4 S BT.</p> <p> A Yew, 12" dia., bears S.37°W., 15 lks.</p>
<p>Wilford Haines - Survey date unknown, filed Dec. 1965 - C.S. File 54/16-23G</p> <p>-----</p> <p>Found - 12" Yew (stub) S.37°W., 15 lks., with scribe. 50" Fir (stub) N.37°E., 12 lks., no scribe visible. Corner stone in place.</p> <p>Scribed- 12" Cedar, S.60°E., 24.0 ft. 12" Fir, N.59°W., 57.2 ft.</p>
<p>Weyerhaeuser Co. - 1963 - C.S. File 53/108-11</p> <p>-----</p> <p>Fd - 1884 stone in place. 50" Fir, N.37°E., 7.9 ft., high stump, face deeply burned out. 12" Yew, S.37°W., 9.9 ft., burned stump, portions of orig. scribing. Haines T iron stake in good condition alongside stone Haines' 16" Cedar BT., scribed face still open. Haines' 16" Fir BT., scribed face healed over.</p> <p>BTs - 16" Cedar, S.57°E., 22.7 ft. "W" nail & Plate added. 16" Fir, N.60°W., 56.4 ft., "W" nail & Plate added.</p>
<p>Ken Hoffine, LS 2291 - For: Lone Rock Timber Co. - Jan. 1990 - M 109-56 - C.S. File 63/106</p> <p>-----</p> <p>Found - Wilford Haines' 3/4" T-iron with identification button top of bar adjacent to orig. 1884 12"x18" buried stone with faint markings on West face and the following accessories:</p> <p> Orig. 12" Yew bears s.37°W., 10 ft. This is a 10 ft. tall burned decayed snag, no visible scribe.</p> <p> Orig. 50" D.Fir bears N.44°E., 11.0 ft. Heavily decayed 4' tall snag, no visible scribe.</p> <p> 20" Cedar stump, bears S.57°E., 22.7 ft. Well healed scar cut through w/Weyco tag & "W" spike.</p> <p> 16" D.Fir stump bears N.60°W., 56.0 ft. Very low cut stump with no evidence remaining.</p> <p> 10" Hemlock, bears S.27°W. 11.3', I tagged this tree</p> <p>Corner lies on a steep West facing slope, 30' North of creek which flows NW & approx. 100' east of end of old logging rd.</p> <p style="text-align: right;">Cont.</p>

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Dan Baker - For: Weyerhaeuser Co. - Dan Hunyada & Sean Bowen
Crew - 2/2008 (filed 3/29/2017) - C.S. File 65/95-18

Found - Haines "T" iron - 8" above ground.
50" rotten fir stump, N.44°E., 11.6 ft. to center.
26" Cedar stump, S.59°E., 22.9 ft.
20" Hemlock, S.28°W., 11.2 ft.
12" Yew stump, S.37°W., 10.0 ft.

New - 7" Fir, N.6°E., 16.8 ft. to center, scribed "X BT"
6" Fir, S.42°E., 14.6 ft. to center, scribed "X BT"
9" Alder, N.64°W., 51.3 ft to center, scribed "X BT"
Set 6 ft. metal post alongside corner.

Note - The north ½ of the west line of sec. 25 was
traversed, blazed and painted by Baker &
Associates in Feb. 2008. The west ½ of the north
line of sec. was traversed, blazed, and painted
by Baker & Associates also in Feb. 2008.
Basis of bearing for this survey was the West ½ of
the north line of sec. per the 1856 GLO survey.
Ground cover: Salal & sm Fir (clear cut to south)
Slope face (bearing) N.65°E. -18%