

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - William P. Wright, Deputy Surveyor, under Contract No. 514, dated Aug. 27, 1884 (DCSO records Vol. 6 Page(s) 2303)

Set post 4" dia., 4 ft. long, with marked stone marked T23S S24 on NE, R4W S25 on SE, S26 on SW, S23 on NW face with 1 notch on E & 2 on S from which

- A Fir, 50" dia., bears N.25°W., 7 lks., mkd: T23S R4W S23 BT.
- A Cedar, 8" dia., bears N.22°E., 47 lks., mkd: T23S R4W S24 BT.
- A Fir, 36" dia., bears S.53°E., 63 lks., mkd: T23S R4W S25 BT.
- A Fir 36" dia. bears S.15°W., 54 lks. mkd: T23S R4W S26 BT

Wilford Haines - Survey date unknown, filed Dec. 1965 - C.S. File 54/16-23H

Found - 50" Fir, N.25°W., 7 lks., snag no scribe.
8" Cedar, N.22°E., 47 lks., scribe shows.
36" Fir, S.53°E., 63 lks., down
36" Fir, S.15°W., S.15°W., 54 lks., down.

Scribed- 26" Cedar, S.28°E., 11.6 ft.
6" Cedar, S.44°W., 20.3 ft.
14" Cedar, N.70°W., 49.5 ft.

Weyerhaeuser Co. - 1963 - C.S. File 53/108-10

Found - Stone, not fd., but corner is under large windfall.
8" Cedar N.22°E., 31.0 ft., face open & good scribing visible.
36" Fir, S.53°E., 41.6 ft., stump hole of large, rotted Fir windfall.
36" Fir, S.15°W., 35.6 ft., rotted broken stump.
50" Fir, N.25°W., 4.6 ft., 56" snag, no scribing found, possibly bark scribed where recent windfall scraped this face of tree.
Wilford Haines' "T" iron stake.

BTs - 14" Cedar N.21°E., 30.0 ft. (OBT) "W" nail & plate added.
26" Cedar S.27°E., 10.5 ft., (Haines) "W" nail & plate added.
6" Cedar S.44°W., 20.0 ft., (Haines) "W" nail & plate added.
12" Cedar N.68°W., 48.7 ft., (Haines) "W" nail & plate added.

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by James E. Jelly, Cadastral Surveyor, under Group #1083, surveyed Nov. 1981/Apr. 1982 (DCSO records Vol. 46 Page(s) 17541)

For the sec. cor. perpetuated by Haines during an unrecorded survey, date unknown, monumented with a "T" shaped iron rod, 3/4" dia., firmly set, projecting 12" above ground, with a steel washer, 1" dia., mkd: Wilford Haines 239 Survey Point Drain, Ore., from which the remains of the orig. BTs:

A Cedar, 25" dia., bears N.22°E., 47 lks., with fragmentary scribe marks visible on partially healed blaze.

A root hole, bears S.53°E., 63 lks., with a down fir alongside, 36" dia., no marks visible.

A Fir stump, size indeterminate, bears S.15°W., 54 lks., no marks visible.

A Fir stump, 72" dia., bears N.25°W., 11 lks., no marks visible. (Rec. 7 lks.)

and BTs mkd. by Haines

A Cedar, 34" dia., bears S.27°E., 17 lks., with healed blaze.

A Cedar, 15" dia., bears S.44°W., 30 lks., with healed blaze.

A Cedar, 27" dia., bears N.70°W., 75 lks., with healed double blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T24S R4W	
S 23	S 24
S 26	S 25
1981	

Reset iron rod alongside iron post.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2168, Surveyed May/Nov. 2007 - DCSO records Vol. 57 Pages 22581-2

The cor. of secs 23, 24, 25, & 26, monumented with an iron post, 2½" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd.

from which the remains of the orig. bearing trees

A cedar, 37" dia., bears N.22°E., 31.0 ft., with a healed blaze.

A decayed fir stump, size indeterminate, bears S.15°W., 38.4 ft., with no marks visible. (Record, 35.6 ft.)

A sawed, decayed fir stump, 72" dia., bears N.25°W., 7.3 ft., with no marks visible. continued next page

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remains of BTs mkd. by Haines, date unknown
A cedar, 41" dia., bears S.27°E., 11.2 ft., with a healed blaze.
A cedar, 28" dia., bears S.44°W., 19.8 ft., with a healed blaze.
A cedar snag, 28" dia., bears N.70°W., 49.5 ft., with no marks visible.
and new bearing tree
A fir, 11" dia., bears N.80¾°W., 32.3 ft., mkd. T23S R4W S23 BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

Daniel Baker - For: WEYCO - 2/2008 - C.S. File 65/95-5

Found - 3¼" brass cap "1981"
35" cedar, N.21°E., 31.4' to center.
42" cedar, S.30°E., 10.1' to center.
59" Fir Roothole, S.53°E., 65.2' to center.
Rotten Fir stump, S.15°W., 38.6' to center.
28" Cedar, S.46°W., 20.3' to center.
11" Fir, N.78°W., 32.3' to center.
27" Cedar snag, N.71°W., 49.3' to center.
64" Fir stump, N.30°W., 7.7' to center.
Note - 6 ft. metal post alongside corner.