

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - William P. Wright, Deputy Surveyor, under Contract No. 514, dated Aug. 27, 1884 (DCSO records Vol. 6 Page(s) 2305)

-----  
Set post 4" dia., 4 ft. long, with marked stone 12" in ground for ¼ sec. cor. mkd: ¼ S on W face, from which  
A Fir, 48" dia., bears N.60°E., 22 lks., mkd: ¼ S BT.  
A Fir, 18" dia., bears S.87°W., 70 lks.

Wilford Haines - Survey date unknown, filed Dec. 1965 - C.S. File 54/16-23M

-----  
Found - 48" Fir, N.60°E., 22 lks., stump.  
18" Fir, S.87°W., 70 lks., alive and part of bark scribe visible.  
Scribed- 6" Hemlock, N.45°E., 4.2 ft.  
Re-bark scribed Fir to West.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Stone - Jerry Layne - Nov. 1965 - C.S. File 54/16-30

-----  
Found - Haines' "T" iron at corner. (Not recorded)  
Orig. 48", now 50" Fir stump N.60°E., 14.5 ft., no scar, no scribe fd.  
Orig. 18", now 36" Fir, S.87°W., 46.2 ft. (face) "¼" bark scribe very old in poor condition, "363 ¼ S23 BT". (Rescribed above old scribe - BT alive & in good condition.  
8" Hemlock N.37°E., 4.8 ft., unrecorded, mkd: ¼ S24 BT & Haines' button on face, leaning badly.  
New BTs- 6" Yew, N.21°W., 34.6 ft. mkd: ¼ S23 CS BT  
10" Hemlock, N.52°E., 14.7 ft. mkd: ¼ S24 CS BT.

Donald Branch, L.S. 1137 - For: U.S. Bank - April 1987 - M 104-1 and C.S. 63/48

-----  
Found - Haines' "T" iron.  
BTs - A 36" Fir stump bears S.88°W., 46.2 ft. to face per Rec.  
8" Yew, N.24°W., 34.6 ft. with healed blaze and tag. NE BT down.  
New BT - 6" Hemlock bears N.88°E., 11.1 ft. scribed "X" BT and L.S. washer in the blaze.

(Cont. next page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ken Hoffine - For: Juniper Properties Ltd. - Aug. 1994 - M 120-66.

-----

CONDITION REPORT ONLY

- Found - Haines T-Iron 0.7 ft. above ground.
- 8" Hemlock bears N.88°E., 11.1 ft. 'x' carved in face, we tagged.
- 58" Fir stump bears N.65°E., 17.2 ft. has Haines button, no tag.
- 13" down and broken hemlock bears N.46°E. (tag shows N.52°E) 14.7 ft. scribing visible on standing base.
- 10" Yew bears N.24°W., 34.2 ft. vis. scribing in face with BLM tag.
- 36" Fir stump covered with tin cap bears S.88°W., 46.2 ft. to the face, has Haines button. Bark scribed. We tag tree.

Note - Corner lies in gentle ground among re-prod to the west and young trees to the east.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2168, Surveyed May/Nov. 2007 - DCSO records Vol. 57 Page(s) 22592-3

-----

The ¼ sec. cor. of secs. 23 & 24, perpetuated by Haines, date unknown, perpetuated by Tracy, in 1965, perpetuated by Branch, in 1987, monumented with a "T" shaped iron rod, 1" dia., firmly set, projecting 9" above ground, with 1" dia. brass disk mkd. WILFORD N HAINES 239 DRAIN ORE affixed to top, from which the remains of the orig. bearing trees

A sawed decayed fir stump, 52" dia., bears N.60°E., 14.5 ft., with no marks visible.

A tin-capped, decayed fir stump, 34" dia., bears N.88¾°W., 46.2 ft., with no marks visible. (Record, S.87°W.)

and bearing trees mkd. by Tracy

A hemlock, 20" dia., bears N.77¼°E., 19.7 ft., with a healed blaze.

A yew, 10" dia., bears N.21¾°W., 34.2 ft., with a healed blaze.

and remains of a bearing tree mkd. by Branch

A hemlock snag, 9" dia., bears N.87¾°E., 11.0 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, directly over the existing "T" shaped iron rod, with brass cap mkd.

continued next page

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T23S R4W  
                  <sup>1</sup>/<sub>4</sub>  
S 23|S 24  
                  2007

Bury a magnet in a white plastic case at the base of the stainless steel post.