TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855 (DCSO records Vol. 6 Page(s) 2289)

Set ¼ Sec. post from which
A Fir 40" dia., bears N.51°E., 41 lks.
A B.Oak 4" dia., bears N.21°W., 10 lks.

BLM dependent resurvey by James E. Jelly, Cadastral Surveyor, under Group #733, surveyed Apr. 1971 (DCSO records Vol. 35 Page(s) 14539)

Point for the ¼ sec. cor. at proportionate dist; there is no remaining evidence of the orig. corner.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

¼
S 14|S 13
T23S R4W
1971

from which
A Fir, 8" dia., bears N.55½°E., 23½ lks., mkd: ¼ S13 BT.
A Fir, 6" dia., bears S.42½°W., 21½ lks., mkd: ¼ S14 BT.

Fd & used in BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #1083 - Surveyed Nov. 1981/April 1982 (DCSO records Vol. 46 Page(s) 17540-41)

Fd. Ok 6/1991 by Donald Peel - M 113-42
Fd. OK 11/1997 by Les Roberts - M 127-75

BLM resurvey by A. Bert Skeesick Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2147, surveyed Aug/Nov. 2006 - (DCSO rec. Vol. 55 Page(s) 21413)

The ¼ sec. cor. of secs. 13 and 14, monumented with an iron post, 2½" dia., firmly set, projecting 9 ins. above the ground, with brass cap (properly) mkd.
from which a bearing tree mkd. by Jelley in 1971
A fir, 19" dia., bears N.55¼°E., 15.5 ft., with a healed blaze.
and a bearing tree mkd. by Jelley in 1971, reported by Jelley in 1981-82
A fir, 15" dia., bears S.46°W., 14.2 ft., with a healed blaze.