

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs 11, 12, 13, & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records Vol. 6 Page(s) 2289)

Set post for sec. corner from which
A Fir 6" dia., bears S.81°W., 30 lks.
A Fir 18" dia., bears S.79°E., 40 lks.
A Fir 8" dia., bears N.27°W., 295 lks.
A Fir 8" dia., bears N.55°E., 315 lks.

Wilford Haines - For: Whipple Mill, Drain Or. June 1961 -
M 22-6

Found - NW BT
Set - 1" x 1" x 36" T iron & scribed:
10" Fir, N.27°E., 101.2 ft.
12" I.Cedar, S.6°E., 88.9 ft.
8" Fir, S.62°W., 57.7 ft.
18" Fir, N.20°W., 75.2 ft.

BLM dependent resurvey by James E. Jelly, Cadastral Surveyor,
under Group #733, surveyed Apr. 1971 (DCSO records Vol. 35
Page(s) 14540-41)

The sec. cor. perpetuated and recorded by Haines in 1963,
monumented with a 1" T iron, firmly set, projecting 10" above
ground, from which the remaining OBT:
A decayed Fir stump, size indeterminate, bears N.27°W.,
295 lks., no marks remaining.
and BT by Haines
A Fir, 15" dia., bears N.23¼°E., 153 lks., with healed
blaze.
A Cedar, 18" dia., bears S.9½°E., 135 lks., with
fragmentary scribe marks visible on partially healed
blaze.
A Fir, 13" dia., bears S.58¼°W., 87½ lks., with healed
blaze.
A Fir, 20" dia., bears N.23 3/4°W., 114 lks., with scribe
marks S11 T23S R4W BT visible on bark blaze.
At the corner point
Set an iron post, 28" long, 2½" dia., 22" in the ground
directly atop the T iron, with brass cap mkd:
T23S R4W
S 11 | S 12
S 14 | S 13
1971
(Cont. next page)

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs 11, 12, 13, & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which new BTs
A Fir, 6" dia., bears N.68½°E., 18 lks., mkd: T23S R4W S12 BT.
A Fir, 6" dia., bears N.47°W., 14½ lks., mkd: T23S R4W S11 BT.

Fd ok by Les Roberts - 11/1997 - M 127-75

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1955, surveyed 2000/2001. (DCS0 rec. Vol. 54 page(s) 20832-3)

The cor. of secs. 11, 12, 13, & 14, monumented with an iron post, 2½" diam., firmly set, projecting 8" above the ground, with brass cap (properly) mkd.,
from which a bearing tree mkd. by Haines, in 1961,
A fir, 26" dia., bears N.23¾°W., 75.2 ft., with scribe marks S11 T23S R4W BT visible on the bark.
and the remains of a bearing tree mkd. by Jelley
A roothole, bears N.47°W., 9.6 ft., alongside of which is the fir trunk, 11" dia., with a healed blaze.
and new reference monuments
An aluminum rod, 36" long, ¾" dia., set 33" in the ground for a reference monument, bears S.44°22'33"E., 19.9 ft. with aluminum cap mkd. RM T23SR4W S13 19.9 FT TO COR 2001 and an arrow pointing to the corner.
An aluminum rod, 36" long, ¾" dia., set 32" in the ground for a reference monument, bears S.30°32'59"W., 19.4 ft, with aluminum cap mkd. RM T23SR4W S14 19.4 FT TO COR 2001 and an arrow pointing to the corner.