

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records Vol. 6 Page(s) 2289)

Set ¼ Sec. post from which
 A Fir, 8" dia., bears N.45°E., 10 lks.
 A Fir, 8" dia., bears N.58°W., 37 lks.

Wilford Haines - For: Whipple Mill -June 1961 - M 22-6

Found - 8" W.Fir, N.38°W., 37 lks.
Set - 1" x 1" x 36" T. iron & scribed:
 10" Cedar N.40°W., 15.2 ft.
 12" Maple S.28°E., 13.7 ft.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike
Stone - Jerry Layne - Nov. 1965 - C.S. File 54/16-41

Found - Haines "T" iron & BTs as recorded by Haines in 1961
 10" Cedar, alive & in good condition, N.40°W., 15.2
 ft., mkd: "¼ S11 BT" and Haines' button.
 12" Maple, badly injured by falling snag, S.28°E.,
 13.7 ft., mkd: "¼ S12 BT" and Haines' button.
 8", now 20" W.Fir, N.38°W., 24.4 ft., down & pushed
 out of place.
New BT - 11" I.Cedar S.85½°E., 61.4 ft., mkd: ¼ S12 CS BT.
Note - This corner lies approx. 100 ft. S. of new access
 road and 30 ft. N. of creek, course SW.

BLM Dependent resurvey by Timothy J. Moore, Cadastral
Surveyor and Robert H. Browning, Surveying Technician under
Group #1955, surveyed 2000/2001. (DCSO rec. Vol. 54 page(s)
20834-5)

The ¼ sec. cor. of secs. 11 & 12, perpetuated from original
evidence no longer in existence by Haines, in 1961, further
perpetuated by Tracy, in 1965, monumented with a 1x1" "T"
shaped iron rod, firmly set, projecting 5" above the ground,
with brass button, 1" dia., affixed to top, mkd. SURVEY POINT
WILFORD N. HAINES 239 DRAIN ORE, from which the remains of
bearing trees mkd. by Haines
 A maple snag, 16" dia., bears S.29¼°E., 14.3 ft., with a
 healed blaze.
 A cedar, 25" dia., bears N.46½°W., 14.4 ft., with a healed
 blaze.
and the remains of a bearing tree mkd. by Tracy
 A cedar snag, 12" dia., bears S.86°E., 60.6 ft., with
 scribe marks 1/4 S12 BT visible on partially healed
 double blaze. continued next page

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, in a collar of stone, with brass cap mkd.

T 23 S R 4 W

1/4

S 11 | S 12

2001

from which a new bearing tree

A fir, 7" dia., bears N.8¼°E., 26.0 ft., mkd. 1/4 S12 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

Deposit a magnet in a white plastic case at the base of the stainless steel post, and place the "T" shaped iron rod along east side of the stainless steel post