

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 24

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Donald Branch - For: U.S. Bank - April 1987 - M 104-1 ----- Set - 5/8" x 30" iron rod w/LS cap. Spike nail set in stump bears N.0°56'W., 22.60 ft. Spike nail set in stump bears S.80°30'36"E., 29.37 ft.	
Ken Hoffine, Lone Rock Timber Co. - Witness: Gary Angiolet - 4/7/2015 - C.S. File 65/89-16 ----- Found - Reference spike in rotten stump bears S.80°27'35"E., 29.38 ft. Record (S.80°30'36"E., 29.37 ft.) 5/8" Iron Rod With Yellow Plastic Cap Set By Branch New - 8" D.Fir bears S.86½°E., 25.1 ft. We scribe C¼ S24 BT and Nail Aluminum BT Tag To The Tree. 6" D.Fir bears S.3½°W., 24.6 ft. We Scribe C¼ S24 BT and Nail Aluminum BT Tag To The Tree. 6" D.Fir bears N.18¾°W., 6.45 ft. We Scribe C¼ S24 BT and Nail Aluminum Bearing Tree Tag To The Tree Note - We ran a closed loop survey from the C¼ to the N¼ and back to the C¼. We blazed painted and put metal U-Post on true line. The C¼ monument lies on flat ground in stand of 6" to 8" Douglas fir, and is 0.2 ft. above ground. Bearing Basis from Branch Map M104-1	
Daniel Baker - For: WEYCO - 2/2008 - C.S. File 65/95-6 ----- Found - 5/8" iron rod & yellow plastic cap "BRANCH" 10" Fir, S.86°E., 25.1' to center. 8" Fir, S.3°W., 24.5' to center. 8" Fir, N.18°W., 6.5' to center. Spike in 24" Fir stump, S.80°E., 29.4' Note - Set 6 ft. steel post alongside corner.	