

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 12 & 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - Gordon & Gardner, Contract #52 dated Feb. 1855 (DCSO records Vol. 6 Page(s) 2294)</p> <p>-----</p> <p>Set ¼ Sec. post from which A Fir, 50" dia., bears S.14°W., 17 lks. A Fir, 4" dia., bears N.24°E., 61 lks.</p>
<p>Wilford Haines - For: Whipple Mill, Drain Or. June 1961 - M 22-6</p> <p>-----</p> <p>Found - Stub of Orig. Fir BT S.14°W., 17 lks. 1½" I. Pipe in place for corner. Set - 1" x 1" x 36" T-iron by pipe & scribed: 26" Fir, S.11¼°E., 62.1 ft. 20" I.Cedar, N.23°W., 47.4 ft.</p>
<p>Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Stone - Jerry Layne - Nov. 1965 - C.S. File 54/16-43</p> <p>-----</p> <p>Found - Haines "T" iron 1½" I. Pipe & BTs as recorded by Haines in 1961 20", now 28" I.Cedar N.23°W., 47.4 ft., alive, scribe visible. 26", now 28" Fir S.11¼°E., 62.1 ft., dead, struck by lighting. New BTs- 8" D.Fir, S.62°W., 38.5 ft., mkd: ¼ S13 CS BT. Note - This corner lies approx. 30 ft. west of small, marshy creek, course NW.</p>
<p>Fd ok by Les Roberts - 11/1997 - M 127-75</p>
<p>BLM resurvey by A. Bert Skeesick Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2147, surveyed Aug/Nov. 2006 - (DCSO rec. Vol. 55 Page(s) 21414-5)</p> <p>-----</p> <p>The ¼ sec. cor. of secs. 12 and 13, perpetuated by Haines, in 1961, further perpetuated by Tracy, in 1965, monumented with an iron post, 1½" dia., firmly set, projecting 8" above the ground, with no cap, from which the remains of an original bearing tree A decayed fir stump, size indeterminate, bears S.14° W., 11.2 ft., with no marks visible. and the remains of bearing trees mkd. by Haines A decayed fir stump, size indeterminate, bears S.13½°E., 61.1 ft., with no marks visible. A sawed cedar stump, 30" dia., bears N.25½°W., 48.1 ft., with a healed blaze. continued next page</p>

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 12 & 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remains of a bearing tree mkd. by Tracy
A sawed fir stump, 22" dia., bears S. 61½°W., 38.6 ft.,
with a healed blaze.

At the corner point
Set a stainless steel post, 28" long, 2½" dia., 26" in the
ground, directly over the iron pipe, with brass cap mkd.

T23S R4W
¼ S 12
S 13
2006

from which new bearing trees

A fir, 6" dia., bears N.35½°E., 41.0 ft., mkd. ¼ S12 BT.

A fir, 14" dia., bears S.78°E., 79.3 ft. mkd. ¼ S13 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail)
driven at the base right side-center, unless otherwise
described in the corner description

Deposit a magnet in a white plastic case at the base of the
stainless steel post.