

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 12

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Gordon & Gardner, Contract #52 dated Feb. 1855 (DCSO records Vol. 6 Page(s) 2290)

Set ¼ Sec. post from which
 A Fir 40" dia., bears N.28°E., 43 lks.
 A Fir 50" dia., bears S.8°E., 64 lks.

Wilford Haines - For: Woolley, Whipple & Weyerhaeuser Co. Nov. 1963 - M 26-80

Found - Old square stake.
 Stump hole of BT, now windfall, S.8°E., 64 lks.
 3 windfalls NE but could not determine if one was BT
Set - 1"x1"36" T. iron from which a
 12" D.Fir with a "W" spike bears S.16°09'W., 34.1 ft

Weyerhaeuser - July 30, 1963, rec'd. 6/3/1981 - C.S. File 58/8-11 (also & C.S. File 53/108-1)

Found - No trace of orig. post.
 40" now 48" down Fir, N.28°E., moved out of place by old logging. Axe marks only.
 50" Fir, S.8°E., has been down for several years. Burned - no scribing visible - old axe marks.
 "T" iron at point for corner at rec. distance and bearing from SE BT.
New BT - 10" Fir, S.21°W., 34.0 ft. with "W" nail & plate.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Stone - Jerry Layne - Nov. 1965 - C.S. File 54/16-44

Found - Haines' "T" iron & BT as recorded in 1963.
 12" D.Fir S.21°W., 34.1 ft., not scribed, "W" nail at base. Haines' calls bearing S.16°09'W., we re-scribe this tree, "¼ S 12 CS BT"
New BT - 14" R.Cedar N.86°E., 70.0 ft., mkd: ¼ S1 CS BT.
Note - This corner lies in small patch of reproduction of D.Fir, approx. 250.0 ft. S. of edge of big timber.