

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 12; & Sec. 7, T23-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 6 Page(s) 2271)

-----  
Set ¼ sec. post, from which  
A Fir 8" dia., bears N.63°W., 17 lks. dist.  
A Fir 8" dia., bears S.27°E., 25 lks. dist.

-----  
Wilford N. Haines, #239 - For: Woolley, Whipple & Weyerhaeuser Co. - Nov. 1963 - M 26-80

-----  
Set 1" x 1" x 36" T. Iron by proportionate measurement.  
Scribed- 5" D.Fir S.31°E., 6.3 ft.  
6" D.Fir N.15°W., 6.4 ft.

-----  
Glen McChesney - For: Weyerhaeuser Co. - 8/7/1968 - C.S. File 65/45-9A&B (received by DCSO 3/21/2003)

-----  
Found - No OBTs fd.  
"T" iron in place  
6" D.Fir S.31°E., 6.1 ft., to scribed face, scribing visible upper & lower faces.  
8" D.Fir N.15°W., 6.2 ft. to scribed face, scribing visible upper & lower faces.  
Accessories Established:  
6" D.Fir S.30°E., 6.0 ft. (Haines 1963) added "W" nail & plate.  
8" D.Fir N.15°W., 6.0 ft. (Haines 1963) added "W" nail & plate.

-----  
Dave Wellman, LS 2163 - For: Weyerhaeuser Co. - Ryan Shurtliff - 1/31/2003 - C.S. File 65/45-12A&B

-----  
Found - 1" "T" iron 1.0 ft. above ground level  
15" Fir S.27°E., 6.6 ft. to center, closed face - Haines BT.  
15" Fir N.12°W., 5.8 ft. to center, closed face - Haines BT.  
New - 12" Fir, S.86½°W., 28.3 ft. to spike set side center - scribed "¼ S12 BT"  
18" Fir S.71°E., 15.5 ft. to spike set side center - scribed "¼ S7 BT"  
6' Metal fence post 1.0 ft. North.