

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 1; & 6 T23-3W

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 6 Page(s) 2271)  
-----  
Set ¼ post from which  
    A fir, 50" dia., bears N.30°W., 39 lks.  
    A cedar, 12" dia., bears N.84°W., 40 lks.

Herbert R Jones, PE - For: Weyerhaeuser Timber Co. & Camac Veneer Inc. - 7/1959 (DOWNLOADED FROM LANE CO. WEBSITE, FILED W/DCSO & ADDED 4/13/2023) -C.S. File 65/111-42  
-----  
After a diligent and through search was made by engineers employed by the Weyerhaeuser Timber Co. & this engineer, the following corner was considered lost;  
    ¼ corner common to sections 1 & 6, T23S - R3 & 4W  
The following corners were fd & used for control:  
    T22S R4W  $\frac{S36|S31}{S 1|S6}$  R3W AND T23S R4W  $\frac{S 1|S 6}{S12|S 7}$  R3W  
The ¼ corner common to sections 1 & 6 was restored by single proportionate measurement (At a point S.3°26'W. 2636.5 ft from the NE Cor Sec. 1), on true line between sections 1 & 6)  
Set - 1/2" monel metal pipe for ¼ corner.  
Referenced by the Weyerhaeuser method  
    7" Fir S.62°E., 19.2 ft.  
    50" Fir N.39°W., 38.7 ft.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Stone - Nov. 1965 - C.S. File 54/16-15-16  
-----  
Reported as Not Found  
Found - ½" IP at cor. pt & BTs as follows -  
    48" Fir (stump) N.39°W., 38.7 ft. "W" nail & plate - no scribe.  
    9" D.Fir S.62°E., 19.2 ft. "W" nail & plate - no scribed.  
(SEE ABOVE FOR 1959) Weyerhaeuser renewal - We find no trace orig. Cor.

Brent Knapp - For: Weyerhaeuser Co. - 8/2023 - M182-54  
-----  
Found - 1/2" iron pipe  
    48" Fir stump, N.39°W., 38.7'  
    14" Fir stump w/nail & plate; S.62°E., 19.2'  
    11" Fir stump, healed scar & Weyerhaeuser tag;  
        N.14°E., 27.0 (source unknown)  
  
continued next page

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 1; & 6 T23-3W

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New -	17" Fir stump, healed scar & Weyerhaeuser tag; S.35°W., 20.4' (source unknown) 13" Fir, scribed "¼ S1 BT", N.79°W., 42.5' Metal post; S.3°W., 5.0' (on line)
-------	---