

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION NE tsp. cor. (NE Cor. Sec. 1)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A portion of the East Bdy. of T. 22 S., R. 4 W., as surveyed by James E. Freeman, Deputy Surveyor, under Contract No. 1. Dated May 28, 1851 - (DCSO records, Vol. 6 Pg. 2270 A)

Set post for Cor. of Townships 22 & 23 S., Ranges 3 & 4 W.,
A Fir, 40" dia., bears, N.65°E., 39 lks., dist.
A Fir, 16" dia, bears, S.50°E., 40 lks., dist.
A Fir, 17" dia., bears, S.70°W., 60 lks., dist.
A Fir, 12" dia., bears, N.87°W., 102 lks., dist.

(This information was not originally typed in DCSO records, was added on 1/11/96. (by DCSO JC)

U.S. BLM Dependent Resurvey - June 10, 1959 - See notes in C.S. File 54/16-1

Perpetuated with a 1/2" alum. pipe, firmly set, 12" above ground, at record bearing and distance from the only remaining orig. BT:

59" Fir bears N.65°E., 39 lks. with scribe mark "S" and other illegible scribe marks visible on partially open blaze.

Set Iron post 28" long, 2½" dia., 24" in ground with brass cap mkd:

T22S	R4W	S	C	R3W
		S 36		S 31
T23S		S 1		S 6
		1959		

New BTs -7" Madrone bears N.52½°E., 72 lks. mkd. T22S R3W S31 SC BT.

6" Chinquapin bears S.29 3/4°E., 38 lks. mkd. T23S R3W S6 SC BT.

6" Madrone bears S.36°W., 60 lks. mkd. T23S R4W S1 SC BT.

6" Madrone bears N.82½°W., 21 lks. mkd. T22S R4W S36 SC BT.

Deposit local corner marker alongside the iron post.