

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 047050

PRIMARY CORNER DESCRIPTION SW Cor. R. Smith DLC #47

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,
dated Sept. 1854

Set stone 6x8" and one 4x5x6" for SW cor., from which
A B.Oak 10" dia., bears N.5°E., 31 lks.
A B.Oak 10" dia., bears S.85°W., 70 lks.

Survey by Bruce Shaner - For: D.M. Webb - Feb. 1964 - M 27-35

Found-Orig. stone with "C4" visible.
Set 5/8" Iron rod over the stone, from which a:
28" W.Oak BT with face rotted out, but with old axe
marks, bears N.5°E., 20.5 ft.
New -12" D.Fir, scribed "SWC DLC 47" bears S.55°W., 54.5 ft.
30" D.Fir, scribed "SWC DLC 47" bears N.21°E., 110.7 ft.

Fd. OK, Nov. 1980, R. Kimberling, M 86-13
Fd. OK, Dec. 1983, B. Bentz, M 95-78

Douglas County Surveyors Office - Randall Smith & Stephen
Flause - June 2, 1997 - C.S. 64/75-5

Found - 5/8" I.R. protruding 7" above ground. (1964)
Top of a 5" x 5" stone is found 2" below ground,
with the marks "C47". Stone is along north edge
of I.R. (Orig. corner stone).
Orig. SW BT gone
10" now 36" dia. B.Oak, with a partially healed
previously opened rotted blaze no marks visible,
bears N.5°E., 21.5' (rec. N.5°E., 20.5' dist. is
a face measurement) OBT.
30" now 36" dia. 4' high D.Fir stump, with a fully
healed single blaze, bears N.22°E., 112.9' (rec.
N.21°E., 110.7' dist is a face measurement) 1964.
12" now 30" dia. 1½' high D.Fir stump, with a fully
healed single blaze, bears S.57½°W., 55.5' (rec.
S.55°W., 54.5' dist. is a face measurement)
1964.
All Brg's & Dist taken to I.R.
New - Brg's & Dist. taken to I.R.
6" dia. Hawthorn, double blazed and scribed, "SW DLC
47 CS BT", bears N.34°E., 26.6'.
8" dia. W.Oak, double blazed and scribed "SW DLC 47
CS BT", bears N.71½°E., 48'.
19" dia. Maple, double blazed and scribed "SW DLC 47
CS BT", bears S.54½°W., 66'.
Corner lies at intersection of a N-S & E running fence lines
cont.

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 047050

PRIMARY CORNER DESCRIPTION SW Cor. R. Smith DLC #47

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

DCSO-GIS Corner visitation - 11/30/2006 - Typed: 1/20/2011 -
C.S. File 67/33-1

Monument - 5/8" rebar. Comment - OK

Fd 5/8" IR (bears N.0°10'18"W., 978.85' from corner 28, 29,
32, & 33) 7/2018 by D Edwards, M174-55A