TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 31; & S.36, T23-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2342)

Set ¼ sec. post, from which
A Y.Oak 14" dia., bears S.37½°E., 19 lks.
A Y.Oak 13" dia., bears N.2°W., 13 lks.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12635)

The ¼ sec.cor., determined at record bearing and distance from the original bearing trees:
An Oak 20" dia., bears S.37½°E., 19 lks. dist., marks grown over.
An Oak 26" dia., bears N.2°W., 13 lks. dist., marks grown over.
At the corner point
Set an Iron post, 3 ft. long, 1" dia., 27" in the ground, with brass cap mkd: ¼
S 36 S 31
1943

Fd. OK, April 1956, G. Gardner, M 2-61

Fd. OK, July 1993, K. Hoffine, M 117-52