

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 30; and 25, T23-6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2342)

-----  
Set ¼ sec. post, from which  
A Y.Oak 14' dia., bears S.87°W., 125 lks.  
A Y.Oak 14" dia., bears N.55°E., 59 lks.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12636)

-----  
The ¼ sec. cor., determined at record bearing and distance to the remains of the original bearing trees:

An Oak snag 24" dia., bears N.55°E., 59 lks. dist., marks rotted off.

An Oak stump 20" dia., bears S.87°W., 125 lks. dist., marks rotted off.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, with brass cap mkd:

¼  
S25 S30  
1943

from which

A Fir 22" dia., bears N.37°E., 30 lks. dist., mkd. ¼ S30 BT.

A Fir 20" dia., bears N.40½°W., 48 lks. dist., mkd. ¼ S25 BT.

Fd. OK, April 1956, G. Gardner, M 2-61

BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/August 22, 1995 - (DCSO records Vol. 51 Page(s) 19455)

-----  
The ¼ sec. cor. monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

¼  
S25 S30  
1943

from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen

A sawed fir stump, 30 ins. diam., bears N. 37° E., 30 lks. dist., with scribe marks ¼ S30 BT visible on open blaze. (Cont. Next Page)

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 30; & 25 of T23-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed fir stump, 28 ins. diam., bears N. 40½° W., 48 lks. dist., with healed blaze.  
and new bearing trees  
A fir, 22 ins. diam., bears N. 52½° E., 69 lks. dist., mkd. ¼ S30 BT.  
A fir, 10 ins. diam., bears N. 63° W., 24½ lks. dist., mkd. ¼ S25 BT.