

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24 & 25, T23-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2341)

Set post, cor. to secs. 19, 30, 24 and 25, from which

- A Fir 30" dia., bears N.14°E., 40 lks.
- A Fir 28" dia., bears S.19°E., 109 lks.
- A Fir 50" dia., bears S.66½°W., 112 lks.
- A Fir 36" dia., bears N.12½°W., 93 lks.

Cor. Fd. and used in GLO survey by John McQuinn, contract #466, dated April 1883 (DCSO records, Vol. 6 Pg. 2399)

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12637)

The Sec. Cor., determined at record bearing and distance to the original bearing trees:

- A Fir stump 30" dia., bears N.14°E., 40 lks. dist., marks rotted off.
- A Fir stump 30" dia., bears S.19°E., 109 lks. dist., marks rotted off.
- A Fir 60" dia., bears S.66½°W., 112 lks. dist., mkd. BT.
- A Fir stump 36" dia., bears N.12½°W., 93 lks. dist., marks rotted off.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, with brass cap mkd:

T23S
R6W R5W
S24 S19
S25 S30
1943

from which

- A Fir 14" dia., bears N.32°E., 41 lks. dist., mkd. T23S R5W S19 BT.
- A Fir 18" dia., bears S.22°E., 46 lks. dist., mkd. T23S R5W S30 BT.
- A Fir 10" dia., bears N.43°W., 68 lks. dist., mkd. T23S R6W S24 BT.

BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/August 22, 1995 - (DCSO records Vol. 51 Page(s) 19456-57)

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24 & 25, T23-6

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

The cor. of secs. 19, 24, 25, and 30, monumented with an iron post, 2" dia., firmly set, projecting 14" above ground, with brass cap mkd.

T23S	
R6W	R5W
S24	S19
S25	S30

1943

from which the remains of the original bearing trees
 A sawed fir stump, 48" dia., bears S.28°E., 141 lks., no marks visible on opened blaze. (Rec. S.19°E. 109 lks)
 A fir, 65" dia. bears S.65½°W., 104 lks with blaze chopped open and rehealed. (Record, S.66½°W., 112 lks.)
 and the remains of a BT mkd. by Gould, Gawron, and Eggen
 A root hole, bears S. 22° E., 46 lks., alongside of which is lying a fir, 22" dia., with healed blaze.
 and new bearing trees
 A fir, 8" dia. bears N.78½°E., 38 lks mkd. T23S R5W S19 BT
 A fir, 10" dia., bears S.51½°E., 56 lks., mkd. T23S R5W S30 BT.
 A maple, 14" dia., bears N.44°W., 42½ lks., mkd. T23S R6W S24 BT.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2315, Surveyed May/June 2010 - DCSO records Vol. 57 Pages 22769-70

 The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., bears N.89°36'04"W., 2535.88 ft. monumented with an iron post, 2" dia., firmly set, projecting 12" above the ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees
 A sawed fir stump, 41" dia, bears S.28°E., 93.1 ft., with no marks visible on an open blaze.
 A fir, 65" dia., bears S.65½°W., 68.6 ft., with a healed blaze.
 and bearing trees mkd. by Rogers, et at
 A fir, 9" dia., bears N.78½°E., 25.1 ft., with a healed blaze.
 A fir, 18" dia., bears S.51½°E., 37.0 ft., with a healed blaze.
 A maple 15" dia bears N.44°W., 28.1 ft., with scribe marks S24 BT visible on a partially healed blaze.

continued next page

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24 & 25, T23-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2961, surveyed Oct. 2019/Jan. 2020- (DCSO records Vol. 59 Page(s) 24036 & BLM Plat 2022-1 T23-6)

The cor. of secs. 19, 24, 25, and 30, reported by Skeesick in 2010; perpetuated by person(s) unknown; monumented with an iron post, 2" dia., firmly set, projecting 12" above ground, with a brass cap (properly) mkd.

from which the remains of the BTs reported by Skeesick

A fir, 11" dia., bears N.78½°E., 25.1 ft., with a healed blaze.

A roothole bears S.51½°E., 37.0 ft., alongside of which is a down fir, 19" dia., with a healed blaze.

A fir stump, 41" dia., bears S.28°E., 93.1 ft., with no marks visible on open blaze. (Original)

A fir snag, 65" dia., bears S.65½°W., 68.6 ft., with a healed blaze. (Original)

A maple, 16" dia., bears N.44°W., 28.1 ft., with scribe marks BT visible on partially healed blaze.

and a BT mkd. by person(s) unknown

A fir, 34" dia., bears S.6°W., 7.0 ft., with a healed blaze; and with scribe marks BT visible on bark.

and a new bearing tree

A maple, 8" dia., bears S.82¾°E., 43.2 ft., mkd. T23S R5W S30 BT.

(New BT has a) 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.