

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2377)

Set ¼ sec. post, from which
A Laurel 12" dia., bears N.67¼°E., 44 lks.
A Maple 8" dia., bears S.20 3/4°W., 54 lks.

Survey by Daniel Baker - For: Weyerhaeuser Co. - March 15, 1994 - M 118-60

Set 2" x 42" Iron pipe with brass cap mkd: "T23S R5W ¼ S18 S19 PLS 1978 1993", from which
29" Fir N.61°E., 18.6 ft.
28" Fir N.39°E., 16.2 ft.
69" Fir S.49°W., 26.5 ft.
11" Maple S.74°W., 56.0 ft.
Note: 1" Iron pipe with alum. tag mkd: "for BLM use only" wrapped around it, bears S.14°39'26"E., 10.14 ft.

Fd. Ok by Ken Hoffine, 1/2006 - M149-61

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2315, Surveyed May/June 2010 - DCSO records Vol. 57 Page(s) 22773-4

The ¼ sec. cor. of secs. 18 & 19, reestablished by Baker, in 1994, by proportionate measurement, and is accepted as a careful and faithful reestablishment of the cor, monumented with an iron post, 2" dia., firmly set, projecting 12" above the ground, with brass cap (properly) mkd.

from which bearing trees mkd. by Baker
A fir snag, 32" dia., bears N.34¼°E., 17.4 ft., with scribe marks ¼ S18 visible on a partially healed blaze.
A fir, 33" dia., bears N.56¼°E., 19.6 ft., with scribe marks ¼ S18 BT visible on the bark.
A fir, 70" dia., bears S.45½°W 281 ft. with scribe marks ¼ S19 BT visible on a partially healed blaze.
A maple, 15" dia., bears S.71¼°W., 557 ft., with a healed double blaze.

From this cor., a point established by persons unknown, noted by Baker, bears S.14°36'56"E., 10.14 ft., monumented with an iron pipe, 1" dia., firmly set, projecting 12" above the ground, and is not utilized in the course of this survey.

(NAD 1983 (CORS))
Latitude: 43°33'45.92"N. Longitude: 123°20'12.16"W.